

Sorts	Type	Parameters
System	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
	CPU/Image sensor	1/2.9 inch 1080p progressive scan CMOS sensor
	Minimum illumination	0.5 Lux(Color mode), 0. 1 Lux(B&W mode)
	Lens/Viewing angle	3.6mm@F2.0/ 101° Diagonal
	Night vision	IR-CUT with auto-switching , 6PCS IR LED lights; Irradiation distance: 10~ 15 m
	Compression standard	H.264 main profile/Motion-JPEG/JPEG
	Data Rate	Main stream:1296P@ 15fps
	Bit rate/maximum frame rate	128~4096kbps/ 15fps
	Image adjustment	Brightness and contrast are adjustable
Audio	Input	Built-in — 38dB microphone
	Output	Built-in 8Ω2 W speaker
	Sampling frequency/bit width	8KHz/ 16bit
	Compression standard/Bit Rate	G.711/64kbps
Network	Network configuration	QR code, AP network configuration
	Network protocol	TCP/IP, HTTP, TCP, UDP, DHCP, DNS, NTP, P2P etc.
	Wireless network	IEEE802. 11b/g/n ; Supports AP mode
	Wireless frequency	2.4~2.4835GHz
	Wireless security encryption	64/ 128-bitWEP/WPA-PSK/WPA2-PSK data encryption
Pan & Tilt	Pan & Tilt	Pan 345° /Tilt 55°
	Preset position	Supports 16 (Mobile phone App supports 5) preset positions
Storage	Storage functions	Supports T-Flash card(max supports 256GB); Cloud Storage
Alarm	Alarm detection	Radar detection; Humanoid detection
Physical Indicators	Rated voltage	DC5V±5%
	Power supply	Supports four 18650 or four 21700 batteries
	Power	Rated power: 5W (with IR LED lights ON)/Max power: 11W (with Pan & Tilt ON)
	Operating condition	Temperature: - 10~50℃; Humidity: <90%
	Weight	Net: 604g (Note: in kind prevail)
	Package size	205x205x146mm (Note: in kind prevail)

