

### 4G Low Power Parking Security Camera--CB75P

Product image		Product features	
		★ 4G full netcom	
		★ Remote active wake-up, two-way voice intercom	
		★ Quick start, start recording within 400ms	
		★ Intelligent detection of human movement, intelligent alarm push	
		★ Low power system optimization	
		★ Supports China and European versions	
		★ Free Cloud storage	
		★ Small and compact appearance(IR-CUT integrated module, supports 4G)	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors viewing at the same time.
2	Collection	CPU	T31
		Image sensor	GC2083, 1/3 CMOS(Pixel selectable, PCB compatible)
		Minimum illumination	0.3 ~ 0.5Lux(Color mode),0Lux(B&W mode)
		Lens	4G lens, IR-CUT integrated, standard lens diameter 10mm
		Viewing angle	D135° Diagonal
3	Video	Night Vision	Black and white night vision, photosensitive automatically switch after it detects the light change, eight 940nm non luminescent patch infrared lamps with an illumination distance of 3-5 meters.
		Compression standard	H.264 /MJPEF/JPEG
		Data rate	Main stream:1080P/15fps, substream:360P/15fps
		Bit rate	CBR/VBR two rate control modes, with an output rate range of 128 to 4096kbps.
		Image adjustment	Vertical, horizontal adjustable, OSD display.
4	Audio	Input	Built-in-38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/bit rate	G711A
5	AI	Humanoid detection	Humanoid detection, filtering invalid alarm events.
		Intelligent notification sound	Set different notification sounds for different devices, so that you can accurately determine which device is triggered.
		Intelligent alarm sound	Set different alarm sounds based on different scenarios.
6	Network	Networking	Use APP to scan the QR code on device to add/Use the device to scan QR code on APP to add
		Cat1 China	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41
		Cat1 Overseas	European version
7	Key	Key 1	ON/OFF
		Key 2	Mode switch ( 4G mode and DV mode)
		Reset key	Long press to restore factory setting
8	Storage	Local storage	Support TF card (up to 256GB)
		Cloud storage	Free cloud storage
9	Alarm	Alarm detection	Support mobile detection and PIR human detection
10	Physical Indicators	Rated voltage	DC5V±5%
		Consumption	Sleep standby current 5mA, working current: 400-600mA
		Operating condition	Temperature: -10 ~ 50°C; humidity: < 90%
		Weight	Gross weight: TBD ( Note: in kind prevail )
		Size	56×43×44mm(L*W*H)
		Packing list	Camera * 1, bracket * 1, electrostatic sticker * 1, ,manual * 1, SIM card * 1, production introduction card * 1, car step-down line * 1, installation tool * 1, cigarette lighter power supply * 1 (optional), 3-meter USB charging cable * 1 (optional)