| Product Picture # 2.4G/5G dual-band wireless connection, support Bluetooth network configuration # Remote active wake-up, two-way voice intercom # Quick start, start recording within 400ms # Intelligent detection of human movement, intelligent alarm push # \$200mAh battery power supply, low power warning # Dual light source, full color day and night # Free cloud storage alarm videos # Support external solar panels to continuously power the camera. No. Category Type Parameter Operating system Embedded Linux | CB55 | | | |
|--|------------------------|------------------------------|--|--|
| #Remote active wake-up, two-way voice intercom #Quick start, start recording within 400ms #Intelligent detection of human movement, intelligent alarm push #S200mAh battery power supply, low power warning #Dual light source, full color day and night #Free cloud storage alarm videos #Support external solar panels to continuously power the camera. No. Category Type Parameter Operating system Embedded Linux | Product Picture | | Features | |
| #Remote active wake-up, two-way voice intercom #Quick start, start recording within 400ms #Intelligent detection of human movement, intelligent alarm push #S200mAh battery power supply, low power warning #Dual light source, full color day and night #Free cloud storage alarm videos #Support external solar panels to continuously power the camera. No. Category Type Parameter Operating system Embedded Linux | | | ★2.4G/5G dual-band wireless connection, support Bluetooth network configuration | |
| #Quick start, start recording within 400ms # Intelligent detection of human movement, intelligent alarm push #5200mAh battery power supply, low power warning #Dual light source, full color day and night #Free cloud storage alarm videos #Support external solar panels to continuously power the camera. No. Category Type Parameter 1 System Operating system Embedded Linux Online visitor Supports 4 visitors at the same time APP O-KAM Pro CPU T23 Collection Engagement Ov 02010 Lens Focal length 2.8mm Viewing angle Diagonal 144* Night vision Black and white night vision/full color night vision, 2pcs 850nm infrared lights, night vision ran meters, 2pcs white light lights Compression standard H.264 /JPEG 2K, 3 MP, three levels optional Super HD 2304x1296@15fps 768kpbs HD 2304x1296@15fps 512kpbs SD 640x360@15fps 15fps 5512kpbs SD 640x360@15fps 556kpbs Image adjustment 180° rotation Input Built-in = 38dB microphone Unit Built-in = 38dB microphone Unit Built-in = 38dB microphone Unit Built-in = 38dB microphone | | | | |
| *Intelligent detection of human movement, intelligent alarm push *5200mAh battery power supply, low power warning *Dual light source, full color day and night *Free cloud storage alarm videos *Support external solar panels to continuously power the camera. No. Category Type Parameter Operating system Embedded Linux Online visitor Supports 4 visitors at the same time APP O-KAM Pro CPU T23 Image sensor OV 02N10 Lens Focal length 2.8mm Viewing angle Diagonal 144° Night vision Black and white night vision/full color night vision, 2pcs 850nm infrared lights, night vision ran meters, 2pcs white light lights Compression standard H.264 /JPEG 2K, 3 MP, three levels optional Super HD 2304x1296@15fps 768kpbs HD 2304x1296@15fps 512kpbs SD 640x360@15fps 256kpbs Image adjustment 180° rotation Input Built-in 38dB microphone Output Built-in 38dB microphone | | | | |
| *5200mAh battery power supply, low power warning *Dual light source, full color day and night *Free cloud storage alarm videos *Support external solar panels to continuously power the camera. *No.** Category** Type** Parameter Operating system | Vsiacov | | | |
| *Dual light source, full color day and night *Free cloud storage alarm videos *Support external solar panels to continuously power the camera. *No.** Category** Type** Parameter 1 | | | | |
| ** Free cloud storage alarm videos ** Support external solar panels to continuously power the camera. **No.** **Support external solar panels to continuously power the camera. **Departing system** Doperating system** Embedded Llinux | | | ★5200mAh battery power supply, low power warning | |
| Support external solar panels to continuously power the camera. No. Category Type Parameter | | 1 | ★ Dual light source, full color day and night | |
| No. Category Type Parameter Doperating system | | | ★Free cloud storage alarm videos | |
| Operating system Operating system Operating system Online visitor APP O-KAM Pro O-KAM Pro CPU T23 Image sensor OV 02N10 Lens Focal length 2.8mm Viewing angle Diagonal 144° Night vision Black and white night vision/full color night vision, 2pcs 850nm infrared lights, night vision ran meters, 2pcs white light lights Compression standard H.264 /JPEG ZK, 3 MP, three levels optional Super HD 2304x1296@15fps 768kpbs HD 2304x1296@15fps 512kpbs SD 640x360@15fps 256kpbs Image adjustment Input Output Built-in -38dB microphone Output Built-in -38dB microphone Output Built-in -38dB microphone | | | ★Support external solar panels to continuously power the camera. | |
| 1 System Online visitor Supports 4 visitors at the same time APP O-KAM Pro CPU T23 Image sensor OV 02N10 Lens Focal length 2.8mm Viewing angle Diagonal 144° Night vision Black and white night vision/full color night vision, 2pcs 850nm infrared lights, night vision ran meters, 2pcs white light lights Compression standard H.264 /JPEG 2K, 3 MP, three levels optional Super HD 2304x1296@15fps 768kpbs HD 2304x1296@15fps 512kpbs 5D 640x360@15fps 256kpbs Image adjustment 180° rotation Input Built-in —38dB microphone Output Built-in —38dB microphone | Categor | ту Туре | Parameter | |
| APP | | Operating system | Embedded Linux | |
| CPU T23 Image sensor OV 02N10 Lens Focal length 2.8mm Viewing angle Diagonal 144° Night vision Black and white night vision/full color night vision, 2pcs 850nm infrared lights, night vision ran meters, 2pcs white light lights Compression standard H.264 /JPEG 2K, 3 MP, three levels optional Super HD 2304x1296@15fps 768kpbs HD 2304x1296@15fps 512kpbs SD 640x360@15fps 512kpbs SD 640x360@15fps 256kpbs Image adjustment 180° rotation Input Built-in — 38dB microphone Output Built-in — 38dB microphone | 1 System | | | |
| Collection Image sensor OV 02N10 | | | | |
| Lens Focal length 2.8mm Viewing angle Diagonal 144° Night vision Black and white night vision/full color night vision, 2pcs 850nm infrared lights, night vision ran meters, 2pcs white lights Compression standard H.264 /JPEG 2K, 3 MP, three levels optional Super HD 2304x1296@15fps 768kpbs HD 2304x1296@15fps 512kpbs SD 640x360@15fps 512kpbs SD 640x360@15fps 256kpbs Image adjustment 180° rotation Untruit Built-in —38dB microphone Output Built-in —38dB microphone | 2 Collection | | | |
| Viewing angle Diagonal 144° Night vision Black and white night vision/full color night vision, 2pcs 850nm infrared lights, night vision ran meters, 2pcs white light lights Compression standard H.264 /JPEG 2K, 3 MP, three levels optional Super HD 2304x1296@15fps 768kpbs HD 2304x1296@15fps 512kpbs SD 640x360@15fps 512kpbs SD 640x360@15fps 256kpbs Image adjustment Input Built-in — 38dB microphone Output Output Built-in - 801W speaker | | on | | |
| Night vision Black and white night vision/full color night vision, 2pcs 850nm infrared lights, night vision ran meters, 2pcs white light lights Compression standard H.264 /JPEG 2K, 3 MP, three levels optional Super HD 2304x1296@15fps 768kpbs HD 2304x1296@15fps 512kpbs SD 640x360@15fps 512kpbs SD 640x360@15fps 256kpbs Image adjustment Input Built-in — 38dB microphone Output Built-in - 801W speaker | | | | |
| Meters, 2pcs white light lights Compression standard | | | | |
| Compression standard | 3 Video | Night vision | | |
| 2K, 3 MP, three levels optional Super HD 2304x1296@15fps 768kpbs HD 2304x1296@15fps 512kpbs SD 640x360@15fps 256kpbs Image adjustment 180° rotation Input Built-in — 38dB microphone Output Built-in #801W speaker | | Compression standard | | |
| Super HD 2304x1296@15fps 768kpbs | | • | · | |
| HD 2304x1296@15fps 512kpbs SD 640x360@15fps 256kpbs Image adjustment 180° rotation Input Built-in = 38dB microphone Output Built-in 801W speaker County Co | | | | |
| Image adjustment 180° rotation Input Built-in — 38dB microphone Output Built-in 801W speaker | | Pixels | | |
| Input Built-in—38dB microphone Output Built-in 801W speaker | | | SD 640x360@15fps 256kpbs | |
| Output Ruilt-in 801W speaker | | Image adjustment | 180° rotation | |
| Output Built-in 8Ω1W speaker | 4 Audio | Input | Built-in — 38dB microphone | |
| 4 Audio | | Output | Built-in 8Ω1W speaker | |
| Sampling frequency/bit width 8KHz/16bit | | Sampling frequency/bit width | | |
| Compression standard / Bit rate G711A | | | | |
| Humanoid detection Humanoid detection, filtering invalid alarms Area detection Free daub, only monitoring the areas concerned by users | | | | |
| , , , | | | Different devices push different sounds, so that you can know exactly which device is triggered | |
| Al Intelligent alarm sound Set different alarm sounds according to different scenarios | AI | | | |
| Smart assistant Support Alexa | | | | |
| More Al functions (testing) Pets, vehicles, parcels, etc | | | | |
| Wireless frequency 2.4/5.8G | | | | |
| 6 Network Connection AP hotspot network configuration, QR code network configuration, bluetooth network configuration. | 6 Network | Connection | AP hotspot network configuration, QR code network configuration, bluetooth network configuration | |
| 7 Key Key 1 On/Off key | 7 Key | Key 1 | On/Off key | |
| Reset key Long press to restore factory settings | | Reset key | Long press to restore factory settings | |
| 8 Storage External TF card Support TF card (up to 256GB) | Storage | External TF card | Support TF card (up to 256GB) | |
| Cloud storage Free cloud storage | , , , | Cloud storage | · · · · · · | |
| 9 Alarm Alarm detection PIR human detection | Alarm | | | |
| Power saving mode PIR triggered recording 24 hours full time recording (when betters level is about 40%) |) NA/ | Ü | | |
| 10 Working Mode Smart sleep mode 24-hour full-time recording (when battery level is above 40%) Super power saving mode PIR triggered recording, camera cannot be woken up through App | working M | · | - · · · · · | |
| Super power saving mode PIR triggered recording, camera cannot be woken up through App Charging voltage 5V/2A TYPE-C | + | | | |
| Power supply 5200mAh battery, 2*18650, supports external 5V solar panel (maximum support 2*21700) | | | , | |
| Consumption Sleep current 260uA, working current: 230-360mA | 11 Physical Indicators | | | |
| | | | | |
| Weight Net weight: 195g Gross weight: 370g | | | | |
| Size Camera: 92.5*56.3*59mm Pacakaging box: 152*119*79mm | | | | |
| Packing list Camera*1, bracket*1, charging cable*1, manual*1 | | | | |