


C994

Product Image		Features	
		★ F2.0 large aperture, more light intake, clearer night vision	
		★ Full-duplex two-way talk	
		★ Infrared and white light integrated light board, supports full color day and night	
		★ ISP image processing technology, preserving true colors	
		★ Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	VStarcam Ultra
2	Collection	Processor	Tsingmicro TX5110CV206
		Memory	512Mb
		Lens	3.6mm
		Image sensor	1/3.3" GC20C3 1080p progressive scan CMOS sensor
		Min. Illumination	0.5Lux (Color), 0.1Lux (B/W)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Field of View	79 ° diagonal
3	Video	Resolution	1080P 1920x1080/15FPS/2MP; 1296P 2304x1296/15FPS/3MP (interpolation)
		Night vision	Color night vision; Infrared night vision, range 10m
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Vertical adjustment, OSD display
4	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency / Bit depth	8KHz/16bit
		Compression standard/Bit rate	G711A
5	PTZ	Movement range	Pan: 310° Tilt: 115°
6	Network	Network interface	N/A
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G-5.8G
		Wireless security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
7	Storage	External TF card	Support TF card (up to 256GB)
		Cloud storage	Cloud storage supported (subscription required)
8	Alarm	Alarm detection	Motion detection, human detection, human framing,human tracking, and area detection
9	Physical Indicators	Rated voltage	DC5V±5%
		Power consumption	Power: 1.6W (0.32A) Maximum power: 2.75W (0.55A)
		Operating condition	Temperature: -10 ~ 55°C; Humidity: < 90%
		Weight	Net weight: 158g. Gross weight: 338g
		Product Dimension	76x76x116mm
		Package Dimension	90x90x185mm
		Carton Dimension	470x470x395mm
		QTY/CTN	50PCS
Package Contents	Camera ×1, bracket×1, power adapter ×1, power cable ×1, user manual ×1, screw kit ×1		