


| Dual Lens 4G Low Power Battery Camera--CB75D                                      |                     |  |  |
|---|---------------------|--|--|
| Product Image   |                     | Product features   |  |
|  |                     | ★4G full netcom  |  |
|   |                     | ★Remote active wake-up, two-way voice intercom                   |  |
|   |                     | ★400ms quick start   |  |
|   |                     | ★Intelligent detection of human movement, intelligent alarm push |  |
|   |                     | ★3000mAh battery, low battery reminder                           |  |
|   |                     | ★Ultra-low power system optimization                             |  |
|   |                     | ★Free cloud storage to save alarm videos                         |  |
|   |                     | ★Dual lens, long and short focus lens, 6x zoom                   |  |
| No.   | Sorts               | Type   | Parameters   |
| 1   | System              | Operating system   | Linux  |
|   |                     | Online visitor   | Supports 4 visitors at the same time   |
|   |                     | APP  | OKAM PRO   |
| 2   | Collection          | CPU  | T31  |
|   |                     | Memory   | 512Mb  |
|   |                     | Image sensor   | GC2083,1/3 CMOS (pixels optional)  |
|   |                     | Minimum illumination   | 0.3 ~ 0.5Lux(color mode), 0Lux (black and white mode)  |
|   |                     | Lens   | 2.8mm short focal lens + 12mm telephoto lens, IRCUT integrated module  |
|   |                     | Viewing angle  | D135°+35°  |
| 3   | Video               | Night vision   | Black and white night vision, photosensitive will automatically recognize the brightness of light to switch mode, 6*940nm non luminous SMT infrared lamps, IR range 3-5 meters |
|   |                     | Zoom   | 6X zoom  |
|   |                     | Compression standard   | H.264 /MJPEF/JPEG  |
|   |                     | Multi stream   | Main stream: 1080P/15fps, sub stream: 360P/15fps   |
|   |                     | Bit rate   | CBR/VBR two rate control modes, and the output rate range is 128 ~ 4096kbps  |
|   |                     | Image adjustment   | Vertical, horizontal adjustable, OSD display   |
| 4   | Audio               | Input  | Built-in-38dB microphone   |
|   |                     | Output   | Built-in 8Ω1W speaker  |
|   |                     | Sampling frequency/bit width                                     | 8KHz/16bit   |
|   |                     | Compression standard/Bit Rate                                    | G711A  |
| 5   | Network             | Connection method  | Scan the QR code to add device   |
|   |                     | China/CAT1   | FDD:B1/B3/B5/B8<br>TDD:B34/B38/B39/B40/B41   |
|   |                     | Europe/Southeast Asia  | FDD:B1/B3/B7/B8/B20/B28<br>TDD:--  |
| 6   | Key                 | Key 1  | On/Off   |
|   |                     | Key 2  | To switch mode (4G mode and DV mode)   |
|   |                     | Reset key  | Long press to restore factory settings   |
| 7   | Storage             | External TF card   | Supports T-Flash cards (up to 256GB)   |
|   |                     | Cloud storage  | Free cloud storage   |
| 8   | Alarm               | Detection  | Supports human movement detection and PIR human detection  |
| 9   | Physical Indicators | Charging voltage   | DC5V±5%  |
|   |                     | Power supply   | Built in 3000mAh battery   |
|   |                     | Power consumption  | Sleep standby current 5mA, working: 400-600mA  |
|   |                     | Operating condition  | Temperature: -10 ~ 50°C; Humidity: < 90%   |
|   |                     | Weight   | Net weight: 110g   |
|   |                     | Size   | 46.5*60*46.5mm   |
|   |                     | What's in the box  | Camera*1, bracket*1, charging cable*1, manual*1  |