

Dual Lens 4G Low Power Battery Camera--CB75D

Dual Lens 4G Low Power Battery Camera--CB75D			
Product Image			Product features
			★4G full netcom
			★Remote active wake-up, two-way voice intercom
			★400ms quick start
			★Intelligent detection of human movement, intelligent alarm push
			★3000mAh battery, low battery reminder
			★Ultra-low power system optimization
			★Free cloud storage to save alarm videos
			★Dual lens, long and short focus lens, 6x zoom
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	OKAM PRO
2	Collection	CPU	T31
		Memory	512Mb
		Image sensor	GC2083,1/3 CMOS (pixels optional)
		Minimum illumination	0.3 ~ 0.5Lux(color mode), 0Lux (black and white mode)
		Lens	2.8mm short focal lens + 12mm telephoto lens, IRCUT integrated module
3	Video	Viewing angle	D135°+35°
		Night vision	Black and white night vision, photosensitive will automatically recognize the brightness of light to switch mode, 6*940nm non luminous SMT infrared lamps, IR range 3-5 meters
		Zoom	6X zoom
		Compression standard	H.264 /MJPEF/JPEG
		Multi stream	Main stream: 1080P/15fps, sub stream: 360P/15fps
		Bit rate	CBR/VBR two rate control modes, and the output rate range is 128 ~ 4096kbps
4	Audio	Image adjustment	Vertical, horizontal adjustable, OSD display
		Input	Built-in-38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
5	Network	Compression standard/Bit Rate	G711A
		Connection method	Scan the QR code to add device
		China/CAT1	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41
6	Key	Europe/Southeast Asia	FDD:B1/B3/B7/B8/B20/B28 TDD:--
		Key 1	On/Off
		Key 2	To switch mode (4G mode and DV mode)
7	Storage	Reset key	Long press to restore factory settings
		External TF card	Supports T-Flash cards (up to 256GB)
8	Alarm	Cloud storage	Free cloud storage
		Detection	Supports human movement detection and PIR human detection
9	Physical Indicators	Charging voltage	DC5V±5%
		Power supply	Built in 3000mAh battery
		Power consumption	Sleep standby current 5mA, working: 400-600mA
		Operating condition	Temperature: -10 ~ 50°C; Humidity: < 90%
		Weight	Net weight: 110g
		Size	46.5*60*46.5mm
		What's in the box	Camera*1, bracket*1, charging cable*1, manual*1