


Dual Lens 4G Low Power Battery Camera--CB75D

Product Image		Product features	
		★4G full netcom	
		★Remote active wake-up, two-way voice intercom	
		★400ms quick start	
		★Intelligent detection of human movement, intelligent alarm push	
		★3000mAh battery, low battery reminder	
		★Ultra-low power system optimization	
		★1-Day free cloud storage to save alarm videos	
		★Dual lens, long and short focus lens, 6x zoom	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	OKAM PRO
2	Collection	CPU	T31
		Memory	512Mb
		Image sensor	GC2083,1/3 CMOS (pixels optional)
		Minimum illumination	0.3 ~ 0.5Lux(color mode), 0Lux (black and white mode)
		Lens	2.8+12mm dual lens
		Viewing angle	D135°+35°
3	Video	Night vision	Black and white night vision, photosensitive will automatically recognize the brightness of light to switch mode, 6*940nm non luminous SMT infrared lamps, IR range 3-5 meters
		Zoom	6X zoom
		Compression standard	H.264 /MJPEF/JPEG
		Multi stream	Main stream: 1080P/15fps, sub stream: 360P/15fps
		Bit rate	CBR/VBR two rate control modes, and the output rate range is 128 ~ 4096kbps
		Image adjustment	Vertical, horizontal adjustable, OSD display
4	Audio	Input	Built-in-38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
5	Network	Connection method	Scan the QR code to add device
		China/CAT4	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41 WCDMA:B1/B5/B8
		Europe/Southeast Asia	WCDMA : B1/B8 FDD : B1/B3/B7/B8/B20/B28A TDD:B38/B40/B41
6	Key	Key 1	On/Off
		Key 2	To switch mode (4G mode and DV mode)
		Reset key	Long press to restore factory settings
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Lifetime 1-day free cloud storage
8	Alarm	Detection	Supports human movement detection and PIR human detection
9	Physical Indicators	Charging voltage	DC5V±5%
		Power supply	Built in 3000mAh battery
		Power consumption	Sleep standby current 5mA, working: 400-600mA
		Operating condition	Temperature: -10 ~ 50°C; Humidity: < 90%
		Weight	Gross weight: (Note: in kind prevail)
		Size	
		What's in the box	Camera* 1, bracket * 1, TYPE-C charging cable * 1, manual * 1, product card * 1