


## CB77

| Product Image  |                     | Product features   |  |
|--|---------------------|--|--|
|   |                     | ★ Portable. Law enforcement records restore the truth.   |  |
|  |                     | ★ 4G networking, supports remote viewing of on-site conditions anytime, anywhere.                          |  |
|  |                     | ★ 1296P HD resolution  |  |
|  |                     | ★ It supports sound recording, video recording, taking photos. Simultaneous recording of sound and images. |  |
|  |                     | ★ Built in lithium battery for continuous recording of 8 hours.  |  |
|  |                     | ★ 4*940nm patch infrared lights, night vision distance 5 meters; Supports infrared night vision on/off.    |  |
|  |                     | ★ Can manually flip the lens 180 degrees and set the image to flip up and down in the App.                 |  |
|  |                     | ★ Supports multi user sharing, 4 users simultaneous live view  |  |
| ★ Cloud storage. The videos triggered by motion detection will be pushed to the cloud server for storage. No need to fear of losing important videos even if the camera is stolen. |                     |  |  |
| No.  | Sorts               | Type   | Parameters   |
| 1  | System              | Operating system   | Linux  |
|  |                     | Online visitor   | Supports 4 visitors at the same time   |
|  |                     | APP  | O-KAM  |
| 2  | Collection          | CPU  | T31  |
|  |                     | Memory   | 8M   |
|  |                     | Image sensor   | GC2083   |
|  |                     | Minimum illumination   | 0.5Lux (color mode), 0.1Lux (black & white mode)   |
|  |                     | Lens   | GC2083/1G3P  |
|  |                     | Viewing angle  | Diagonal 129°  |
| 3  | Video               | Night vision   | Dual filter automatic switching, 4*940nm patch infrared lights, irradiation distance: 5 meters   |
|  |                     | Compression standard   | H.264 /MJPEF/JPEG  |
|  |                     | Multi stream   | Main stream:1296P/25fps;Sub stream:360P/25fps  |
|  |                     | IR control   | When the IR night vision function is enabled, IR and ICR are automatically detected; when the IR night vision function is disabled, IR is off and ICR is fixed in the day vision mode. |
|  |                     | Bit rate   | CBR/VBR two rate control modes, and the output rate range is 128 ~ 4096kbps  |
|  |                     | Image adjustment   | Vertical, horizontal adjustable, OSD display   |
| 4  | Audio               | Input  | Built-in-38dB microphone   |
|  |                     | Sampling frequency/bit width   | 8KHz/16bit   |
|  |                     | Compression standard/Bit Rate  | G711A  |
| 5  | AI                  | Human detection, human frame   | Human detection, filtering invalid video contents  |
|  |                     | Motion detection   | Motion detection, remote alarm events  |
|  |                     | Area detection   | Free smearing, only monitoring the areas concerned by users  |
| 6  | Network             | 4G China   | FDD:B1/B3/B5/B7/B8/B28   |
|  |                     |  | WCDMA:B1/B5/B8   |
|  |                     | 4G Europe  | FDD:B1/B3/B7/B8/B20/B28  |
|  |                     |  | WCDMA:B1/B8  |
| 7  | Button              | Reset  | Long press to restore factory setting  |
|  |                     | Video button   | Short press to pause the recording and save  |
|  |                     | Photo button   | Short press 1 time to take photos; Short press 2 time to turn on/off night vision  |
|  |                     | Power button   | Push up to turn on, push down to turn off  |
|  |                     |  |  |
| 8  | Storage             | External TF card   | TF card (up to 256GB)  |
|  |                     | Cloud storage  | Free loop cloud storage  |
| 9  | Physical Indicators | Alarm detection  | Motion detection, human detection  |
|  |                     | Charging voltage   | DC5V±5%@Type-C interface   |
|  |                     | Power supply   | 1500mAh battery  |
|  |                     | Power consumption  | Sleep standby: 300uA, working: 400MA-800MA max   |
|  |                     | Operating condition  | Temperature: -10 ~ 50°C; Humidity: < 90%   |
|  |                     | Weight   | Net weight: 59.5g; Gross weight: 110.3g (Note: in kind prevail)  |
|  |                     | Size   | Camera: 95*37*24mm; Packaging box: 105x40x105mm  |
|  |                     | Packing list   | Camera* 1, manual * 1, Type-C cable  |