

CS611Q-X5

| Product Image | | Product features | |
|---|---------------------|---|---|
|  | | ★ 4 MP Ultra HD | |
| | | ★ 5x optical zoom, long-distance high-definition monitoring | |
| | | ★ Soft light design, 24h color imaging | |
| | | ★ ISP image processing technology, preserving true colors | |
| | | ★ Human detection, real time alerts | |
| | | ★ 2.4G/5G WiFi. The wireless signal is strong and stable, and the video won't sutter. | |
| No. | Sorts | Type | Parameters |
| 1 | System | Operating system | Linux |
| | | Online visitor | Supports 4 visitors at the same time |
| | | APP | O-KAM Pro |
| 2 | Collection | CPU | Sigmastar 337DE |
| | | Memory | 1Gbit |
| | | Lens | 5x zoom lens/diagonal 99.3 ° @1X~40.5 °@5X |
| | | Image sensor | 1/2.9 CMOS sensor |
| | | Minimum illumination | 0.01Lux |
| | | Sensor performance | Support automatic white balance, automatic gain control and automatic backlight |
| | | Night Vision | Dual filter automatic switching, 6pcs 850nm infrared lights, 6 high-power white lights, 4 red and blue alarm lights, illumination distance 15-20 meters |
| 3 | PTZ | Pan/Tilt | Pan 310°/Tilt 90° |
| | | Pre-positions | Supports 16 preset positions on PC, 5 on mobile |
| 4 | Video | Resolution | 2688*1520P/25FPS/400w |
| | | Night Vision | Full color night vision, infrared night vision |
| | | Compression standard | H.264+ /H.264 /MJPEF/JPEG |
| | | Bit rate | 128 ~ 4096kbps |
| | | Image adjustment | Brightness, contrast, OSD display |
| 5 | Audio | Input | Built-in -38dB microphone |
| | | Output | Built-in 8Ω2W speaker |
| | | Sampling frequency/bit width | 8KHz/16bit |
| | | Compression standard/Bit Rate | G711A |
| 6 | AI | Humanoid detection | Humanoid detection, filtering invalid video events |
| | | Human tracking | Automatically zooms in and follows the person after it is detected |
| | | Area detection | Customize the zone that is concerned by users |
| | | Smart notification sound | Different devices push different sounds, so that you can know exactly which device is triggered |
| | | Intelligent alarm sound | Set different equipment alarm sounds according to different scenarios |
| 7 | Network | Network interface | 10Mbps/100Mbps adaptive/RJ45 interface |
| | | Network protocol | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc. |
| | | Wireless network | IEEE802.11b/g/n |
| | | Wireless frequency | 2.4GHz/5Ghz |
| | | Wireless security encryption | 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption |
| 8 | Storage | External TF card | Support TF card (up to 256GB) |
| | | Cloud storage | Support cloud storage, can purchase according to your need |
| 9 | Alarm | Alarm detection | Motion detection, human detection, human framing, human tracking, siren sound, and area detection |
| 10 | Physical Indicators | Rated voltage | DC12V±5% |
| | | Power consumption | Power: 7.4W (with infrared light on), Max power: 12.8W |
| | | Operating condition | Temperature: -10 ~ 50°C; Humidity: < 90% |
| | | Weight | (Note: in kind prevail) |
| | | Packing list | Camera, screw pack, warning sticker, screwdriver, user manual |