


**C993**

| Product Image   |  | Features  |  |
|---|--|---|--|
|  |  | ★F2.0 large aperture, more light intake, clearer night vision                       |  |
|   |  | ★Full-duplex two-way intercom   |  |
|   |  | ★Infrared and white light integrated light board, supports full color day and night |  |
|   |  | ★ISP image processing technology, preserving true colors                            |  |
|   |  | ★Human detection, real time alerts  |  |
| No.   | Sorts  | Type  | Parameters   |
| 1   | System   | Operating system  | Linux  |
|   |  | Online visitor  | Supports 4 visitors at the same time   |
|   |  | APP   | VStarcam Ultra   |
| 2   | Collection   | Processor   | Tsingmicro TX5110CV206   |
|   |  | Memory  | 512Mb  |
|   |  | Lens  | 3.6mm  |
|   |  | Image sensor  | 1/3.3" GC20C3 1080pCMOS image sensor   |
|   |  | Min. Illumination   | 0.5Lux (Color), 0.1Lux (B/W)   |
|   |  | Sensor performance  | Support automatic white balance, automatic gain control and automatic backlight compensation |
|   |  | Night vision  | Color night vision, Infrared night vision  |
| 3   | Video  | Resolution  | 1080P 1920x1080/15FPS/2MP : 1296P 2304x1296/15FPS/3MP(Interpolation)                         |
|   |  | Night vision  | 10m  |
|   |  | Compression standard  | H.264 main profile/Motion-JPEG/JPEG  |
|   |  | IR control  | IR-CUT, soft photosensitive control  |
|   |  | Bit rate  | 128 ~ 4096kbps   |
|   |  | Image adjustment  | Vertical flip, OSD display   |
|   |  | 4   | Audio  |
| Output  | Built-in 8Ω1W speaker  |   |  |
| Sampling frequency / Bit depth  | 8KHz/16bit   |   |  |
| Compression standard/Bit rate   | G711A  |   |  |
| 5   | PTZ  | Movement range  | Pan: 325° Tilt: 55°  |
| 6   | Network  | Network interface   | N/A  |
|   |  | Network protocol  | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P  |
|   |  | Wireless network  | IEEE802.11b/g/n  |
|   |  | Wireless frequency  | 2.4G-5.8G  |
|   |  | Wireless security   | 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption  |
| 7   | Storage  | External TF card  | Support TF card (up to 256GB)  |
|   |  | Cloud storage   | Cloud storage supported (subscription required)  |
| 8   | Alarm  | Alarm detection   | Motion detection, human detection, human framing,human tracking, and area detection          |
| 9   | Physical Indicators  | Rated voltage   | DC5V±5%  |
|   |  | Power consumption   | Power: 1.6W(0.32A), Maximum power: 2.75W (0.55A)   |
|   |  | Operating condition   | Temperature: -10 ~ 55°C; Humidity: < 90%   |
|   |  | Weight  | Net weight: 160g. Gross weight: 330g   |
|   |  | Product Dimension   | 75x76x116mm  |
|   |  | Package Dimension   | 90x90x185mm  |
|   |  | Carton Dimension  | 470x470x395mm  |
|   |  | QTY/CTN   | 50PCS  |
| Package Contents  | Camera *1, power adapter *1, power cord *1, user manual *1, screw kit *1, bracket *1 |   |  |