



My safety, My rule!

**Model: C993**

| Sorts                      | Type                          | Parameters   |
|----------------------------|-------------------------------|--|
| <b>System</b>              | Operating system              | Embedded Linux   |
|                            | Online visitor                | Supports 4 visitors at the same time   |
|                            | CPU/image sensor              | 1/4.5 inch high-quality 1 Mbps CMOS image sensor   |
|                            | Minimum illumination          | 0.5 Lux(Color mode), 0.1 Lux(B&W mode)   |
|                            | Lens/viewing angle            | 58.7°  |
|                            | Night vision                  | Dual filter automatic switching, white light, illumination distance 5-10m  |
|                            | Compression standard          | H.264 main profile/Motion-JPEG/JPEG  |
|                            | Data rate                     | Main stream: 1080p(1920×1080)@30fps/1296p(2304×1296)@15fps<br>Substream: 360p(640×360)@15fps   |
|                            | Bit rate /maximum frame rate  | 128~4096kbps/30fps   |
| <b>Audio</b>               | Image adjustment              | Flip up and down   |
|                            | Input                         | Built-in -38d B microphone   |
|                            | Output                        | Built-in 8 Ω 1W speaker  |
|                            | Sampling frequency/bit width  | 8KHz/16bit   |
| <b>Network</b>             | Compression standard/bit rate | G.711/64kbps   |
|                            | Network interface             | No   |
|                            | Network protocol              | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2Petc.  |
|                            | Wireless network              | IEEE802.11b/g/n; Supports AP configuration and Bluetooth connection  |
|                            | Wireless frequency            | 2.4~2.4835GHz  |
| <b>Pan&amp; Tilt</b>       | Wireless security encryption  | 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption  |
|                            | Rotation angle                | Horizontal 355 °/Vertical 60 °   |
| <b>Storage</b>             | Preset position               | Supports 16 presets (mobile app only supports 5)   |
|                            | Storage                       | Supports T-Flash card(max supports 256GB); Cloud Storage; NVR; NAS;  |
| <b>Alarm</b>               | Alarm detection               | Supports motion detection, humanoid detection, human tracking, voice and flash alarm, illumination function, timing white light on/off |
| <b>Physical indicators</b> | Rated voltage                 | DC5V   |
|                            | Power consumption             | Rated 2W   |
|                            | Operating condition           | Temperature: -10~50C; Humidity: <90%   |
|                            | Weight                        | Camera:186g  |
|                            | Package size                  | (Note: in kind prevail)  |