


## CB78-2

Product image		Features	
		★ 3 MP Ultra HD, 4G network high speed module	
		★ Black light color night vision, presenting a colorful image even with no fill lights	
		★ F1.0 large aperture, 4 times more light intake, clearer night vision	
		★ ISP image processing technology, preserving true colors	
		★ Intelligent detection of human movement and intelligent alarm push	
		★ Remote access, view the camera live feed anytime and anywhere	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors viewing at the same time.
		APP	O-KAM Pro
2	Collection	CPU	U SSC335 (B version) QFN88
		Memory	512Mb
		Lens	4mm F1.0
		Image sensor	1/2.9 CMOS sensor
		Minimum illumination	0.01Lux
		Sensor performance	Supports automatic white balance, automatic gain control, and automatic backlight compensation.
		Night vision	Color night vision
4	Video	Viewing angle	Diagonal: 95 °
		Resolution	2304*1296P/25FPS/3MP
		Compression standard	H.264+ /H.264 /MJPEF/JPEG
		IR control	No IRCUT, full-color night vision
		Bit rate	128 ~ 4096kbps
5	Audio	Image adjustment	Brightness, contrast, OSD display
		Input	Built-in 42dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
6	AI	Humanoid detection	Humanoid detection, filtering invalid alarm events.
		Area detection	Customize detection zones, only monitor areas that matter.
		Intelligent notification sound	Set different notification sounds for different devices, so that you can accurately determine which device is triggered.
		Intelligent alarm sound	Set different alarm sounds based on different scenarios.
	Network	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2Petc.
		4G(China)	FDD:B1/B3/B5/B8
			TDD:B34/B38/B39/B40/B41
			WCDMA:B1/B5/B8
		4G(Europe)	FDD: B1/B3/B5/B7/B8/B20
			TDD:B38/B40/B41
			WCDMA: B1/B5/B8
8	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
9	Alarm	Alarm detection	Supports motion detection, human detection, human framing,siren alarm, and area detection
10	Physical Indicators	Rated voltage	DC5V±5%
		Operating condition	Temperature: -10~55℃; Humidity: <90%
		Camera size	40.5*39*57.5mm
		Weight	Net weight: 65.5g
		What's in the box	Camera, bracket, manual, charging cable