CB78W

☆3 MP Ultra HD	
☆Black light color night vision, presenting a colorful image even with no fill lights	
☆F1.0 large aperture, 4 times more light intake, clearer night vision	
☆ISP image processing technology, preserving true colors	
☆Intelligent detection of human movement and intelligent alarm push	
☆Remote access, view the camera live feed anytime and anywhere	

No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors viewing at the same time.
		APP	O-KAM Pro
2	Collection	CPU	Sigmastar 335
		Memory	1Gbit
		Lens	4mm F1.0
		Image sensor	1/2.9 CMOS sensor
		Minimum illumination	0.01Lux
		Sensor performance	Supports automatic white balance, automatic gain control, and automatic backlight compensation.
		Night vision	Color night vision
		Viewing angle	Diagonal: 91 °, horizontal: 77.3 °, vertical: 42.9 °
3	Video	Resolution	1296*1080P/25FPS/3MP
		Compression standard	H.264+ /H.264 /MJPEF/JPEG
		IR control	No IRCUT, full-color night vision
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
4	Audio	Input	Built-in-38dB microphone
		Output	Built-in 8Ω2W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
5	AI	Humanoid detection	Humanoid detection, filtering invalid alarm events.
		Area detection	Customize detection zones, only monitor areas that matter.
		Intelligent notification sound	Set different notification sounds for different devices, so that you can accurately determine which device is triggered.
		Intelligent alarm sound	Set different alarm sounds based on different scenarios.
6	Network	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4GHz
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
8	Alarm	Alarm detection	Supports motion detection, human detection, human framing, human tracking, siren alarm, and area detection
9	Physical Indicators	Rated voltage	DC5V±5%
		Power consumption	Power:/W Maximum power:/W
		Operating condition	Temperature: -10～55℃; Humidity: ＜90%
		Weight	Gross weight:　（Note: in kind prevail)
		What's in the box	/