Product Image			Features
			★F2.0 large aperture, more light inputs, clearer night vision
			★ Dual light source, supports full-color night vision
			★ ISP image processing technology, preserving true colors
			★ Human detection, real time alerts
No.	Sorts	Туре	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic
		Memory	512Mb
		Lens	4mm
		Image sensor	1/3.27" 1080p progressive scan CMOS sensor
		Minimum	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight
		Night vision	Black and white night vision, full-color night vision
			Diagonal : 82 °
		Viewing angle	
3	Video	Resolution	1080P 1920x1080/15FPS/2 MP; 1296P 2304x1296/15FPS/3 MP
		Night vision	5-10 meters
		Compression	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
	Audio	Input	Built-in -38dB microphone
4		Output	Built-in 8Ω1W speaker
7		Sampling	8KHz/16bit
		Compression	G711A
5	Pan/Tilt	Rotation angle	Not supported
6	Network Storage	Network interface	N/A
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4~5G
		Wireless security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
		External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
8	Alarm	Alarm detection	Motion detection, human detection, human framing, and area detection
	Physical Indicators	Rated voltage	DC5V±5%
		Power consumption	Power: 1.75W (0.35A); Maximum power: 3.25W (0.65A)
		Operating condition	Working temperature: -10~45 °C, working humidity<90%
9		<del> </del>	N.W:77g, G.W:198g
9		Weight	
		Camera size	56x56x99mm
		Packaging box size	103x88x60mm
		Carton size	460x430x330mm , 100PCS/CARTON
<u> </u>			