


C992DR

| Product Image | | Product features | |
|---|---------------------|---|--|
|  | | ★Dual lens dual views, monitor with no blind spots | |
| | | ★F2.0 large aperture, multiple light inputs, clearer night vision | |
| | | ★ISP image processing technology, preserving true colors | |
| | | ★Human detection, real time alerts | |
| No. | Sorts | Type | Parameters |
| 1 | Collection | Operating system | Linux |
| | | Online visitor | Supports 4 visitors at the same time |
| | | APP | O-KAM Pro |
| 2 | Collection | CPU | Ingenic |
| | | Memory | 512Mb |
| | | Lens | 4mm |
| | | Image sensor | 1/4.5 inch high-quality 1 Mbps CMOS image sensor |
| | | Min. Illumination | 0.5Lux (color mode), 0.1Lux (b&w mode) |
| | | Sensor performance | Support automatic white balance, automatic gain control and automatic backlight compensation |
| | | Night vision | Black and white night vision, full-color night vision |
| | | Lens/Viewing angle | Diagonal 58.7° |
| 3 | Video | Resolution | 1080P |
| | | Night vision | Black and white night vision, full-color night vision |
| | | Compression standard | H.264 main profile/Motion-JPEG/JPEG |
| | | IR control | IR-CUT, soft photosensitive control |
| | | Bit rate | 128 ~ 4096kbps |
| | | Image adjustment | Brightness, contrast, OSD display |
| 4 | Audio | Input | Built-in -38dB microphone |
| | | Output | Built-in 8Ω1W speaker |
| | | Sampling frequency/bit | 8KHz/16bit |
| | | Compression standard/Bit | G711A |
| 5 | Pan&tilt | Rotation angle | H: 320° V: 65° |
| 6 | Network | Network interface | 10Mbps/100Mbps |
| | | Network protocol | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P |
| | | Wireless network | IEEE802.11b/g/n |
| | | Wireless frequency | 2.4G |
| | | Wireless security | 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption |
| 7 | Storage | External TF card | Supports T-Flash cards (up to 256GB) |
| | | Cloud storage | Support cloud storage, users can purchase according to their needs. |
| 8 | Alarm | Alarm detection | Motion detection, human detection, human framing, person tracking, and area detection |
| 9 | Physical Indicators | Rated voltage | DC5V±5% |
| | | Power consumption | (Note: in kind prevail) |
| | | Operating condition | Working temperature: -10~55 °C, working humidity<90% |
| | | Weight | N.G: 181g G.W: 300g |
| | | Camera size | 75x76x127mm |
| | | Packaging size | 90x90x185mm |