Low Power Dome Camera-CB65			
Product Image			Product features
			★Wireless connection
	1		★Remote active wake-up, two-way voice intercom
			★Quick start, start recording within 400ms
			★ Intelligent detection of human movement, intelligent alarm push
		0000	★6000 mAh battery, low battery reminder
			★Low power system optimization
			★ Free cloud storage to save alarm videos
			★Dual light source, full color day and night
			★Low power and corded power compatible design
lo.	Sorts	Туре	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	T23
		Internal storage	512Mb
		Image sensor	GC2083,1/3CMOS
		Min. Illumination	0.8Lux/F1.4 (color mode),0.3Lux/F1.4(B&W mode)
		Lens	Standard lens diameter 14mm
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight
		PTZ Viewing angle	Horizontal 305 °, vertical 100 ° D100°
		Night vision	Full color night vision, dual light source, 6 dual color light
3	Video	Compression standard	H 264 /MJPEF/JPEG
		Multi stream	Main stream:1296P/15fps, sub stream:360P/15fps
		ID control	When the IR night vision function is enabled, IR and ICR are automatically detected; when t
		IR control	IR night vision function is disabled, IR is off and ICR is fixed in the day vision mode.
		Bit rate	CBR/VBR two rate control modes, and the output rate range is 128~4096kbps
		Image adjustment	Vertical, horizontal adjustable, OSD display
4	Audio	Input Output	Built-in-38dB microphone Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
			G711A
5	AI	Humanoid detection	Humanoid detection, filtering invalid video content
		Area detection	Free daub, only monitoring the areas concerned by users
			Different devices push different sounds, so that you can know exactly which device is
		Smart notification sound	
		Intelligent alarm sound	Set different equipment alarm sounds according to different scenarios
		More AI functions (testing)	Pets, vehicles, parcels, etc
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P,IPV4
6	Network	Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4~2.4835GHz
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
		Connection	AP hotspot network configuration, QR code network configuration, bluetooth connection
7	Key	Key1	Power ON/OFF
	-,	Reset key	Long Press to restore the factory settings
8	Storage	External TF card Cloud storage	Support TF card (up to 256GB) Free loop cloud storage
		Audible and visual alarm	Sound and light alarm, 6 infrared light and 6 white light, full-color night vision
9	Alarm	Alarm detection	Supports human detection, PIR infrared human detection 10 meters
10	Physical Indicators	Rated voltage	DC5V±5%
		Power supply	6000mAh battery,3*18650
		Power consumption	Sleep current 300uA, working: 230ma-1.5A max
		Operating condition	Temperature: -10 ~ 55°C; Humidity: < 90%
		Weight	G.W.: TBD (Note: in kind prevail)
		Size	Camera: 135*118*133mm
	Packing list		Camera* 1, type-c charging cable * 1, manual * 1