


CS621DR

Product image		Features	
		★Dual lens dual view leaves no blind spots	
		★F2.0 large aperture, more light inputs, clearer night vision	
		★ISP image processing technology, preserving true colors	
		★Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic
		Memory	512Mb
		Lens	4mm
		Image sensor	1/2.7 inch 1080p progressive scan CMOS sensor
		Minimum illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Viewing angle	Diagonal 91°
4	Video	Resolution	1080P 1920x1080/15FPS/2 MP
		Night vision	Black and white night vision, full-color night vision
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
5	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit	8KHz/16bit
		Compression	G711A
6	Pan/Tilt	Rotation angle	Pan: 270° tilt: 90°
7	Network	Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
		Wireless security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
8	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
9	Alarm	Alarm detection	Motion detection, human detection, human framing, siren sound, and area detection
10	Physical Indicators	Rated voltage	DC12V±5%
		Power consumption	Power: 6.24W (0.52A) Maximum power: 9.96W (0.83A)
		Operating condition	Working temperature: -10~55 °C, working humidity<90%
		Weight	N.W.: 233g G.W.: 410g
		Camera size	148x123x185mm
		Packaging box size	180x146x210mm
		Carton size	555x435x465mm , 18PCS/CARTON