


## CG610Q

Product Image		Product features	
		★4K 8MP	
		★Starlight night vision, clear at night	
		★ISP image processing technology, preserving true colors	
		★Human detection, real time alerts	
		★Remote access, view the monitoring areas anytime and anywhere	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		App	OKAM PRO
2	Collection	CPU	Ingenic T41
		Memory	1Gbit
		Lens	4mm
		Image sensor	1/2.7 CMOS sensor
		Minimum	0.01Lux
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight
		Night Vision	6 warm lights and 6 infrared lights
		Viewing angle	Diagonal: 109° Horizontal: 92.9° Vertical: 51°
3	Video	Resolution	3840*2160P/25FPS/8 MP
		Night Vision	Infrared night vision, full color night vision
		Compression	H.265/MJPEG/JPEG
		IR control	When the IR night vision function is enabled, IR and ICR are automatically detected;
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
4	Pan&Tilt	Rotation angle	Pan 260°/ Tilt 88°
5	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8 Ω 2W speaker
		Sampling	8KHz/16bit
		Compression	G711A
6	AI	Humanoid detection	Humanoid detection, filtering invalid video events
		Object tracking	Human tracking, automatically following after detecting a person
		Area detection	Free daub, only monitoring the areas concerned by users
		Smart notification	Different devices push different sounds, so that you can know exactly which device is
		Intelligent alarm	Set different equipment alarm sounds according to different scenarios
7	Network	4G China	FDD:B1/B3/B5/B8
			TDD:B34/B38/B39/B40/B41
			WCDMA:B1/B5/B8
8	Storage	External TF card	Support TF card (up to 256GB)
		Cloud storage	Support cloud storage
9	Alarm	Alarm detection	Motion detection, human detection, human framing, human tracking, siren sound, and
10	Physical Indicators	Rated voltage	DC12V±5%
		Power consumption	Power: 5.2W (infrared light on) Maximum power: 11.7W
		Operating condition	Temperature: -10 ~ 55°C; Humidity: < 90%
		Weight	(Note: in kind prevail)
		Packing list	Camera, screw pack, warning sticker, screwdriver, manual