


**C992DR**

Product Image		Product features	
		★Dual lens dual views, monitor with no blind spots	
		★F2.0 large aperture, multiple light inputs, clearer night vision	
		★ISP image processing technology, preserving true colors	
		★Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic
		Memory	512Mb
		Lens	4mm
		Image sensor	1/4.5 inch high-quality 1 Mbps CMOS image sensor
		Min. Illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision, full-color night vision
		Lens/Viewing angle	Diagonal 58.7°
3	Video	Resolution	3MP lens
		Night vision	Black and white night vision, full-color night vision
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
4	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit	8KHz/16bit
		Compression standard/Bit	G711A
5	Pan&tilt	Rotation angle	H: 320° V: 65°
6	Network	Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
		Wireless security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
8	Alarm	Alarm detection	Motion detection, human detection, human framing, person tracking, and area detection
9	Physical Indicators	Rated voltage	DC5V±5%
		Power consumption	(Note: in kind prevail)
		Operating condition	Working temperature: -10~55 °C, working humidity<90%
		Weight	N.G: 181g G.W: 300g
		Camera size	75x76x127mm
		Packaging size	90x90x185mm