

CB70

Product Image			Product Features
			★4G stable connection
			★Remote active wake-up
			★Quick start, start recording within 400ms
			★Intelligent detection of human movement, intelligent alarm push
			★2000mAh battery, low battery warning
			★Low power system optimization
			★Free cloud storage to save alarm videos
			★Removable bracket
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	T23
		Internal storage	512Mb
		Image sensor	GC2083, 1/3 CMOS (Pixel optional, PCB compatible)
		Min. Illumination	0.3 ~ 0.5Lux (color mode),0Lux (B&W mode)
		Lens	Lens diameter 10mm , 4G lens
		Viewing angle	D135°
3	Video	Night vision	Black and white night vision, photosensitive automatic recognition of light switching, 8pcs 940nm
		Compression standard	H.264 /MJPEF/JPEG
		Multi stream	Main stream: 1296P/15fps Sub stream: 360P/15fps
		Bit rate	CBR/VBR two rate control modes, and the output rate range is 128~4096kbps
		Image adjustment	Vertical, horizontal adjustable, OSD display
4	Audio	Input	Built-in-38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit	G711A
5	AI	Humanoid detection	Humanoid detection, filtering invalid video contents
		Area detection	Free daub, only monitoring the areas concerned by users
		Smart notification sound	Different devices push different sounds, so that you can know exactly which device is triggered
		Intelligent alarm sound	Set different equipment alarm sounds according to different scenarios
		More AI functions (testing)	Pets, vehicles, parcels, etc
6	Network	Connection	Scan the QR code of the device to add/Scan the QR code of the App
		China Cat1	FDD: B1/ B3/ B5/ B8 TDD: B34/ B38/ B39/ B40/ B41
		Overseas Cat4	LTE - FDD: B1/ B3/ B7/ B8/ B20 LTE -TDD: B40/ B41
7	Key	Key 1	On/Off
		Key 2	WIFI/DV mode swiching
		Reset key	Long press to restore the factory settings
8	Storage	External TF card	Support TF card (up to 256GB)
		Cloud storage	Free loop cloud storage
9	Alarm	Detection	PIR human detection
10	Physical Indicators	Rated voltage	DC5V±5%
		Power supply	Built in 2000mAh
		Power consumption	Sleep standby current 5mA, working: 400-600mA
		Operating condition	Temperature: -10 ~ 55°C; Humidity: < 90%
		Weight	G.W.: TBD (Note: in kind prevail)
		Size	52×37×40mm(L x W x H)
		Packing list	Camera*1, bracket*1, MICRO USB*1, manual*1