

CB70W

Product Image		Product features	
		★Wireless connection	
		★Remote active wake-up	
		★Quick start, start recording within 400ms	
		★Intelligent detection of human movement, intelligent alarm push	
		★2000mAh battery, low battery warning	
		★Low power system optimization	
		★Cloud storage to save alarm videos	
		★Removable bracket	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	T23
		Internal storage	512Mb
		Image sensor	GC2083, 1/3 CMOS (Pixel optional, PCB compatible)
		Min. Illumination	0.3 ~ 0.5Lux (color mode), 0Lux (B&W mode)
		Lens	Lens diameter 10mm , 4G lens
3	Video	Viewing angle	D135°
		Night vision	Black and white night vision, photosensitive automatic recognition of light switching, 8pcs 940nm
		Compression standard	H.264 /MJPEF/JPEG
		Multi stream	Main stream: 1296P/15fps Sub stream: 360P/15fps
		Bit rate	CBR/VBR two rate control modes, and the output rate range is 128~4096kbps
4	Audio	Image adjustment	Vertical, horizontal adjustable, OSD display
		Input	Built-in-38dB microphone
		Output	No speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit	G711A
5	AI	Humanoid detection	Humanoid detection, filtering invalid video contents
		Area detection	Free daub, only monitoring the areas concerned by users
		Smart notification sound	Different devices push different sounds, so that you can know exactly which device is triggered
		Smart alarm sound	Set different equipment alarm sounds according to different scenarios
		More AI functions (testing)	Pets, vehicles, parcels, etc
6	Network	Network protocol	TCP/IP, HTTP, TCP, UDP, DHCP, DNS, NTP, P2P, IPV4
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4/5GHz
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
		Connection	AP hotspot networking, Scan QR code to connect
7	Key	Key 1	On/Off
		Reset key	Long press to restore the factory settings
8	Storage	External TF card	Support TF card (up to 256GB)
		Cloud storage	Support
9	Alarm	Detection	PIR human detection
10	Physical Indicators	Rated voltage	DC5V±5%
		Power supply	Built in 2000mAh
		Power consumption	Sleep standby current 5mA, working: 400-600mA
		Operating condition	Temperature: -10 ~ 55°C; Humidity: < 90%
		Weight	G.W.: TBD (Note: in kind prevail)
		Size	52×37×40mm(L x W x H)
		Packing list	Camera*1, bracket*1, MICRO USB*1, manual*1