


CG667DR

Product Image		Features	
		★ Stable 4G connection	
		★ Dual lens recording, leaving no blind spots	
		★ ISP image processing technology, preserving true colors	
		★ Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic
		Memory	512Mb
		Lens	4mm
		Image sensor	1/2.7" 1080p progressive scan CMOS sensor
		Minimum illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight
		Night vision	Black and white night vision, full-color night vision
		Viewing angle	Horizontal: 360° Vertical: 123°
3	Video	Resolution	1080P 1920x1080/15FPS/2 MP; 1296P 2306x1296/15FPS/3 MP
		Night vision	Black and white night vision, full-color night vision
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
4	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling	8KHz/16bit
		Compression	G711A
5	Pan/Tilt	Rotation angle	Pan: 270° Tilt: 90°
6	Network	Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc
		4G China	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41 WCDMA:B1/B5/B8
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
8	Alarm	Alarm detection	Motion detection, human detection, human framing, siren sound, and area detection
9	Physical Indicators	Rated voltage	DC12V±12%
		Power consumption	Power: 7.9W (0.65A) Maximum power: 11W (0.91A)
		Operating condition	Working temperature: -10~55 °C, working humidity<90%
		Weight	N.W: 475g; G.W: 675g
		Camera size	143x168x200mm
		Packaging box size	205x205x146mm
		Carton size	605x425x430mm,16PCS/Carton