

CS996

Product Image			Features
			★ F2.0 large aperture, more light inputs, clearer night vision
			★ Dual core light panel, color night vision
			★ ISP image processing technology, preserving true colors
			★ Human detection, real time alerts
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic
		Memory	512Mb
		Lens	4mm
		Image sensor	1/2.7 inch 1080p progressive scan CMOS sensor
		Minimum illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision, color night vision
		Viewing angle	Diagonal : 91 °
3	Video	Resolution	1080P 1920x1080/15FPS/2MP; 1296P 2304x1296/15FPS/3MP
		Night vision	Black and white night vision, color night vision
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
4	Audio	Image adjustment	Brightness, contrast, OSD display
		Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
5	Pan&Tilt	Compression standard/Bit Rate	G711A
6	Network	Angle	Pan: 345° Tilt: 115°
		Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4,5.2 5.4 or5.8G
7	Storage	Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
		External TF card	Supports T-Flash cards (up to 256GB)
8	Alarm	Cloud storage	Support cloud storage, users can purchase according to their needs.
9	Physical Indicators	Alarm detection	Motion detection, human detection, human framing, area detection,human tracking
		Rated voltage	DC5V±12%
		Power consumption	Power: 2.1W (0.42A) Maximum power: 3.25W (0.65A)
		Operating condition	Working temperature: -10~55 °C, working humidity<90%
		Weight	N.W:190g G.W:332g
		Camera size	84x84x117mm
		Packaging box size	90x90x185mm
Carton size	470x470x395mm,50PCS/carton		