

CS996DR			
Product Image			Features
			★Dual lens dual view leaves no blind spots
			★F2.0 large aperture, more light inputs, clearer night vision
			★WiFi connection
			★Active defense; the device triggers sound-light alarm upon intrusion
			★Support remote monitoring via mobile and PC clients, view live footage anytime anywhere
			★ISP image processing technology, preserving true colors
			★Dual-core light board, 24/7 full-color
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	VStarcam Ultra
2	Collection	Processor	Tsingmicro TX5110CV206
		Memory	512Mb
		Lens	4mm
		Image sensor	1/3.3" GC20C3 1080p progressive scan CMOS sensor
		Minimum illumination	0.5 Lux (Color), 0.1 Lux (B/W)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Color Night Vision, Infrared Night Vision
		Field of View	79 ° diagonal
3	Video	Resolution	1080P 1920x1080/15FPS/2 MP； 1296P 2304x1296/15FPS/3 MP(Interpolation)
		Night vision	5-10m
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
4	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency / Bit depth	8KHz/16bit
		Compression standard/Bit rate	G711A
5	PTZ	Movement range	Pan： 310° Tilt： 90°
6	Network	Network interface	N/A
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
		Wireless security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
7	Storage	External TF card	Support TF card (up to 256GB)
		Cloud storage	Cloud storage supported (subscription required)
8	Alarm	Alarm detection	Motion detection, human detection, human framing, area detection, human tracking
9	Physical Indicators	Rated voltage	DC5V±5%
		Power consumption	Power: 1.6W (0.32A) , max power: 2.75W (0.55A)
		Operating condition	Temperature: -10 ~ 45°C; Humidity: < 90%
		Weight	N.W:206g G.W:386g
		Product Dimension	84x84x117mm
		Package Dimension	90x90x185mm
		Carton Dimension	470x470x395mm
		QTY/CTN	50PCS
		Package Contents	Camera ×1, Bracket×1, Power Adapter ×1, Power Cable ×1, User Manual ×1, Screw Kit ×1