


## CS996DR

Product Image			Features
			★Dual lens dual view leaves no blind spots
			★F2.0 large aperture, more light inputs, clearer night vision
			★ISP image processing technology, preserving true colors
			★Dual channel real-time recording, guarding multiple directions
			★Human detection, real time alerts
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic
		Memory	512Mb
		Lens	4mm
		Image sensor	1/2.7" 1080p progressive scan CMOS sensor
		Minimum illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision, full-color night vision
		Viewing angle	Diagonal : 91 °
3	Video	Resolution	1080P 1920x1080/15FPS/2 MP; 1296P 2304x1296/15FPS/3 MP
		Night vision	Black and white night vision, full-color night vision
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
4	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
5	Pan&Tilt	Angle	Pan: 310° Tilt: 91°
6	Network	Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
8	Alarm	Alarm detection	Motion detection, human detection, human framing, area detection
9	Physical Indicators	Rated voltage	DC5V±5%
		Power consumption	Power: 2.75W (0.55A), max power: 4.9W (0.98A)
		Operating condition	Working temperature: -10~45 °C, working humidity<90%
		Weight	N.W:206g G.W:355g
		Camera size	84x84x117mm
		Packaging box size	90x90x185mm
		Carton size	470x470x395mm, 50PCS/ Carton