С	9	9	6
C	J	J	O

C996				
Product image			Features	
			★F2.0 large aperture, more light intake, clearer night vision	
			★ Dual core light panel, full-color night vision	
			★ISP image processing technology, preserving true colors	
			★ Human detection, real time alerts	
No.	Sorts	Туре	Parameters	
1		Operating system	Linux	
	System	Online visitor	Supports 4 visitors at the same time	
		APP	O-KAM Pro	
		CPU	Ingenic	
		Memory	512Mb	
		Lens	4mm	
	• " "	Image sensor	1/4.5 inch high-quality 1 M CMOS image sensor	
2	Collection	Min. Illumination	0.5Lux (color mode), 0.1Lux (b&w mode)	
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight	
		Night vision	Black and white night vision, full-color night vision	
		Viewing angle	Diagonal 58°	
		Resolution	720P 1280x720/15FPS/1MP; 1080P 1920x1080/15FPS/2MP	
3		Night vision	Black and white night vision, full-color night vision	
		Compression standard	H.264 main profile/Motion-JPEG/JPEG	
	Video	IR control	IR-CUT, soft photosensitive control	
		Bit rate	128 ~ 4096kbps	
		Image adjustment	Brightness, contrast, OSD display	
		Input	Built-in -38dB microphone	
4		Output	Built-in 8Ω1W speaker	
	Audio	Sampling frequency/bit width	8KHz/16bit	
		Compression standard/Bit	G711A	
5	Pan/Tilt	Rotation angle	Pan: 310° Tilt: 115°	
6		Network interface	10Mbps/100Mbps	
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P	
	Network	Wireless network	IEEE802.11b/g/n	
		Wireless frequency	2.4G	
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption	
+		External TF card	Supports T-Flash cards (up to 256GB)	
7	Storage	Cloud storage	Support cloud storage, users can purchase according to their needs.	
8	Alarm	Alarm detection	Motion detection, human detection, human framing, person tracking, and area detection	
	Physical Indicators	Rated voltage	DC5V±12%	
9		Power consumption	Power: 2.1W (0.42A) Maximum power: 3.25W (0.65A)	
		Operating condition	Working temperature: -10~45 °C, working humidity<90%	
		Weight	Net weight: 190g Gross weight: 332g	
		Camera size	84x84x117mm	
		Packaging box size	90x90x185mm	
		Carton size	470x470x395mm, 50PCS/CARTON	
		Gai 1011 5120	TO ATT OXOGORITING OUT OUT OTHER	