

CG621SR

Product image				Features
				★ Three views, monitor with no blind spots
				★ F2.0 large aperture, more light inputs, clearer night vision
				★ ISP image processing technology, preserving true colors
				★ Human detection, real time alerts
No.	Sorts	Type	Parameters	
1	System	Operating system	Linux	
		Online visitor	Supports 4 visitors at the same time	
		APP	O-KAM Pro	
2	Collection	CPU	Ingenic	
		Memory	512Mb	
		Lens	4mm	
		Image sensor	1/2.7" 1080p progressive scan CMOS sensor	
		Min. Illumination	0.5Lux (color mode), 0.1Lux (b&w mode)	
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight	
		Night vision	Black and white night vision, full-color night vision	
		Viewing angle	91°	
3	Video	Resolution	1080P/1920x1080/15FPS	
		Night vision	Black and white night vision, full-color night vision	
		Compression standard	H.264 main profile/Motion-JPEG/JPEG	
		IR control	IR-CUT, soft photosensitive control	
		Bit rate	128 ~ 4096kbps	
		Image adjustment	Brightness, contrast, OSD display	
4	Audio	Input	Built-in -38dB microphone	
		Output	Built-in 8Ω1W speaker	
		Sampling frequency/bit	8KHz/16bit	
		Compression standard/Bit	G711A	
5	Pan/Tilt	Rotation angle	Pan: 270° Tilt: 90°	
6	Network	Network interface	10Mbps/100Mbps	
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P	
		4G network(China)	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41 WCDMA:B1/B5/B8	
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)	
		Cloud storage	Support cloud storage, users can purchase according to their needs.	
8	Alarm	Alarm detection	Motion detection, human detection, human framing, siren alarm, and area detection	
9	Physical Indicators	Rated voltage	DC12V±5%	
		Power consumption	Power: 7.44W (0.62A) Maximum power: 10.92W (0.91A)	
		Operating condition	Working temperature: -10~55 °C, working humidity<90%	
		Weight	N.W.: 600g, G.W.: 1180g	
		Camera size	154x235x185mm	
		Packaging box size	166x209x255mm	
		Carton size	525x433x525mm,12PCS/CARTON	