


CG621SR

Product image		Features	
		★ Three views, monitor with no blind spots	
		★ F2.0 large aperture, more light inputs, clearer night vision	
		★ ISP image processing technology, preserving true colors	
		★ Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic
		Memory	512Mb
		Lens	4mm
		Image sensor	1/2.7" 1080p progressive scan CMOS sensor
		Min. Illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight
		Night vision	Black and white night vision, full-color night vision
		Viewing angle	91°
3	Video	Resolution	1080P/1920x1080/15FPS
		Night vision	Black and white night vision, full-color night vision
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
4	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit	8KHz/16bit
		Compression standard/Bit	G711A
5	Pan/Tilt	Rotation angle	Pan: 270° Tilt: 90°
6	Network	Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		4G network(China)	FDD:B1/B3/B8 TDD:B34/B38/B40
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
8	Alarm	Alarm detection	Motion detection, human detection, human framing, siren alarm, and area detection
9	Physical Indicators	Rated voltage	DC12V±5%
		Power consumption	Power: 7.44W (0.62A) Maximum power: 10.92W (0.91A)
		Operating condition	Working temperature: -10~55 °C, working humidity<90%
		Weight	N.W.: 600g, G.W.: 1180g
		Camera size	154x235x185mm
		Carton size	255x210x165mm
		Carton size	525x435x525mm,12PCS/CARTON