


CV331G

Product image		Features	
		★ One click call button, two-way video call	
		★ 2000mA battery, no fear of power outage	
		★ Warm atmosphere night light	
		★ ISP image processing technology, preserving true colors	
		★ Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic T23
		Memory	512Mb
		Lens	4mm F2.0
		Image sensor	1/2.7 inch 1080p progressive scan CMOS sensor
		Minimum illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision, little night light
		Viewing angle	Diagonal: 91 °
4	Audio	Resolution	1080P 1920x1080/15FPS/2MP; 1296P 2304x1296/15FPS/3MP
		Night vision	Black and white night vision, little night light
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
		Display screen	2.4inch
5	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
6	Pan/Tilt	Rotation angle	Horizontal: 320°, Vertical: Not supported
7	Network	Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		4G network(China)	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41 WCDMA:B1/B5/B8
	Battery	Capacity	2000mAh
8	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
9	Alarm	Alarm detection	Motion detection, human detection, human framing, and area detection
10	Physical Indicators	Rated voltage	DC5V±5%
		Power consumption	Power: 2.36W Maximum power: 4.73W; Charging current: 500mA
		Operating condition	Working temperature: -10~55 °C, working humidity<90%
		Weight	Net weight: 233g, gross weight 383g
		Camera size	83x83x107mm
		Packing box size	90x90x185mm
		Carton size	470x470x395mm, 50PCS/Carton