


CG64

Product Image		Features	
		★ Pan&tilt, two way audio	
		★ Black and white night vision, full color night vision	
		★ ISP image processing technology, preserving true colors	
		★ Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic T23
		Memory	512Mb
		Lens	4mm F2.0
		Image sensor	1/2.7" 1080p progressive scan CMOS sensor
		Minimum illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision, full-color night vision
		Viewing angle	91°
3	Video	Resolution	1920x1080/15FPS/2MP, 1080P; 2304x1296/15FPS/3MP, 1296P
		Night vision	Black and white night vision, full-color night vision
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
4	Audio	Image adjustment	Brightness, contrast, OSD display
		Input	Built-in -38dB microphone
4	Audio	Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
		Rotation angle	Pan: 265° tilt: 95°
5	Pan/Tilt	Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		4G network (China)	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41 WCDMA:B1/B5/B8
6	Network	Alarm detection	Motion detection, human detection, human framing,human tracking , siren alarm and area detection
		Rated voltage	DC12V±5%
7	Alarm	Power consumption	Power: 4.32W (0.37A) Maximum power: 9.84W (0.82A)
		Operating condition	Working temperature: -10~55 °C, working humidity<90%
		Weight	Net weight: 460g; Gross weight: 840g
		Camera size	171x112x179mm
		Packaging box size	195x205x130mm
		Carton size	545x425x415mm, 16PCS/CARTON
		8	Physical Indicators