


## CS621ZR

Product image		Features	
		★ Three lens camera: one fixed lens + two hybrid zoom lens	
		★ F2.0 large aperture, more light inputs, clearer night vision	
		★ ISP image processing technology, preserving true colors	
		★ Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic
		Memory	512Mb
		Lens	4mm+4mm+12mm
		Image sensor	1/2.7" 1080p progressive scan CMOS sensor
		Minimum illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision, full color night vision
		View angle	4mm: 91°; 12mm: 29°
3	Video	Resolution	1080P 1920x1080/15FPS/2MP; 1296P 2304x1296/15FPS/3MP
		Night vision	Black and white night vision, full color night vision
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
4	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
5	Pan/Tilt	Rotation angle	Pan: 270° tilt: 90°
6	Network	Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
7	Storage	Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
		External TF card	Supports T-Flash cards (up to 256GB)
8	Alarm	Cloud storage	Support cloud storage, users can purchase according to their needs.
		Alarm detection	Motion detection, human detection, human framing, human tracking, siren sound, and area detection
9	Physical Indicators	Rated voltage	DC12V±5%
		Power consumption	Power: 6.24W (0.52A) Maximum power: 9.96W (0.83A)
		Operating condition	Working temperature: -10~55 °C, working humidity<90%
		Weight	Net weight: 512g Gross weight: 812g
		Camera size	148x123x185mm
		Packaging box size	182x141x210mm
		Carton size	562x435x450mm,18PCS/CARTON