BG57			
Product Picture			Features
			★4G connection
			★ Remote active wake-up, two-way voice intercom, 180° horizontal rotation
			★ Quick start, start recording within 400ms
			★ Intelligent detection of human movement, alarm push, white light deterrance, customize alarm
		0.	★5200mAh battery power supply, low power warning
			*Dual light source, black and white night vision + full color night vision + starlight night vision can be
			★ Free cloud storage to alarm videos
		-1	★Support 5V solar panel, continuously power supply, and the camera won't not powered off
			★Support sharing device with multiple family members
			★Flexible installation
			★AI function
No.	Sorts	Туре	Parameters
	System	Operating system	Linux
1		Online visitor	Supports 4 visitors at the same time
		APP CPU	O-KAM Pro
2	Collection	Image sensor	T23 OV 02N10
		Lens	Focal lenght 2.8mm
		Viewing angle	Diagonal144°
3	Video	Night vision	Black and white night vision/full color night vision, 2pcs 850nm infrared lights, night vision range 5~8
			meters, 2pcs white light lights
		Compression standard Pixels	H.264 /JPEG 2K, 3 MP, three levels optional
			Super HD 2304x1296@15fps 768kpbs
			HD 2304x1296@15fps 512kpbs
			SD 640x360@15fps 256kpbs
		Image adjustment	180° rotation
4	Audio	Input Output	Built-in — 38dB microphone Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard / Bit rate	G711A
5	Pan & Tilt	Rotation angle	Horizontal rotation 180°
	Al	Human detection Area detection	Human detection, filtering invalid video contents Free daub, only monitoring the areas concerned by users
			Different devices push different sounds, so that you can know exactly which device is triggered(Not
6		Smart notification sound	supported by some mobile phones, such as Huawei)
		Intelligent alarm sound	Set different equipment alarm sounds according to different scenarios
		More Al functions (testing)	Pets, vehicles, parcels, etc
7	Network	Networking	Use APP to scan the QR code on device to add; Use the device to scan QR code on APP to add; FDD:B1/B3/B5/B8
		Chinese version	TDD:834/B38/B39/B40/B41
		American version	FDD: B2/4/5/12/13/25/26
		European version	FDD: B1/B3/B7/B8/B20/B28
8	Key	On/Off	Turn on/off
\vdash	-	Reset key External TF card	Long press to restore factory settings Support TE card (up to 256GP)
9	Storage	Cloud storage	Support TF card (up to 256GB) Free loop cloud storage
10	Alarm	Alarm detection	Support PIR human detection
11	Working Mode	Power saving mode	PIR triggered recording
		AOV mode	24-hour time-lapse recording, when human figure is recognized or PIR triggered recording
		Smart sleep mode	24-hour full-time recording (when battery level is above 40%)
12	Physical Indicators	Super power saving mode Charging voltage	PIR triggered recording, camera cannot be woken up through App 5V/2A TYPE-C
		Power supply	5200mAh battery
		Consumption	Sleep standby current 5mA, working current: 400-600mA
		Operating condition	Temperature: -10 ~ 55°C; Humidity: < 90%
		Weight	Net weight: 270g
		Size	Camer: 114*66*55mm Camera*1 (including bracket), screw package*1, user manual*1, iron sheet*1, nail-free adhesive*1,
		Packing list	auxiliary sticker*1 (Type-C charging cable*1, solar panel*1, solar panel bracket*1 optional)
		Packing list	auxiliary sticker*1 (Type-C charging cable*1, solar panel*1, solar panel bracket*1 optional)