BG621DR			
	Pr	oduct Image	Product features
			AOV ultra-low power consumption, 24-hour video recording, and long-lasting battery life
			Ultra-wide-angle, pan 270° tilt 90°
			Color night vision, black & white night vision, 11pcs dual-color dual light source lights, clearer night vision
			Al algorithm, smart tracking, human feature analysis and framing
			Dual lens dual views;
			Customizable alarm sound, multiple application scenarios
			Free cloud storage
10.	Sorts	Туре	Parameters
_		Operating system	Linux
1	System	Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	T23ZN
		Internal storage Image sensor	512MB GC2083+GC2083+GC2083
		Min. Illumination	0.8Lux/F1.4(color mode),0.3Lux/F1.4(B&W mode)
		Lens	Panorama camera: focal length 4mm, 1G3P Panorama camera: focal length 4mm(1G3P)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Pan&tilt	Horizontal 270°, Vertical 90°
		Viewing angle	D100°
3	Video	Night vision	Color night vision, dual light sources, 11pcs dual-color dual light source lights
		Compression standard	MJPEF/JPEG
		Multi stream	Mainstream:1080P/15fps, sub stream:360P/15fps
		IR control	When the IR night vision function is enabled, IR and ICR are automatically detected; when the IR night vision
		Dit rate	function is disabled, IR is off and ICR is fixed in the day vision mode.
		Bit rate Image adjustment	CBR/VBR two rate control modes, and the output rate range is 128~4096kbps Vertical, horizontal adjustable, OSD display
		Input	Built-in-38dB microphone
	Audio	Output	Built-in 8Ω1W speaker
4		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
		Human detection	Human detection, filtering invalid video contents
5		Area detection	Free daub, only monitoring the areas concerned by users
	Al		
		Smart notification sound	Different devices push different sounds, so that you can know exactly which device is triggered
		Intelligent alarm sound	Set different equipment alarm sounds according to different scenarios
		More Al functions (testing)	Pets, vehicles, parcels, etc
6	Network	Networking	Use APP to scan the QR code on device to add; Use the device to scan QR code on APP to add
		Cat1 China	FDD:B1/B3/B5/B8
		Cati Cilina	TDD:B34/B38/B39/B40/B41
		Cat4 Overseas	European/Japanese/American versions
7	Key/interface Storage	Key 1	On/Off key
		Reset key	long press to restore factory settings
		External TF card	Support TF card (up to 256GB)
		Cloud storage	Free loop cloud storage
9	Alarm	Sound light alarm	Sound and light alarm, 11 infrared + 11 white lights, full color night vision
	AWITT	Alarm detection	Support human detection, PIR detection range: 10 meters
		Rated voltage	DC5V±5%
		Power supply	Built in 8000mAh battery
	1	Consumption	Sleen standby 300uA working: 400MA-1 8A may

Sleep standby 300uA, working: 400MA-1.8A max
Working temperature: -10 ~ 55°C, working humidity <90%

Net weight: 680g
Camera: 183*164*122mm
Camera*1, manual*1, solar panel*1, solar panel bracket*1

Consumption

Weight
Size
Packing list

Operating condition

Physical Indicators