| BG621TR | | | |
|---------|--------------------------|-------------------------------|--|
| | Pro | oduct Image | Product features |
| | | - | ★ Stable 4G connection |
| | | 1 | ★ Remote active wake-up, two-way voice intercom |
| | | | ★ Quick start, start recording within 400ms |
| | | | ★ Intelligent detection of human movement, intelligent alarm push |
| | | | ★8000mAh battery, low battery warning |
| | | | ★ Low power system optimization |
| | | | ★ Free cloud storage to save alarm videos |
| | 6 | *** | ★ Dual lens to monitor two different areas simultaneously |
| | | • • | ★ Dual lens linkage, automatic zoom |
| | | | ★ Dual light source, full color day and night |
| | | | ★ Low power and corded power compatible design |
| No. | Sorts | Туре | Parameters |
| 1 | System | Operating system | Linux |
| | | Online visitor | Supports 4 visitors at the same time |
| | | APP | O-KAM Pro |
| 2 | Collection | CPU | T23ZN |
| | | Internal storage | 512MB |
| | | Image sensor | GC2083+GC2083+GC2083 |
| | | Min. Illumination | 0.8Lux/F1.4(color mode),0.3Lux/F1.4(B&W mode) |
| | | | |
| | | Lens | Panorama camera: focal length 4mm,1G3P; Tracking camera: focal length 4mm(1G3P)+12mm (1G |
| | | Sensor performance | Support automatic white balance, automatic gain control and automatic backlight compensation |
| | | Pan&tilt | Horizontal 270°, Vertical 90° |
| | | Viewing angle | D100° |
| 3 | Video | Night vision | Color night vision, dual light sources, 11pcs dual-color dual light source lights |
| | | Compression standard | MJPEF/JPEG |
| | | Multi stream | Mainstream: 1080P/15fps, sub stream: 360P/15fps |
| | | IR control | When the IR night vision function is enabled, IR and ICR are automatically detected; when the IR night |
| | | IK COILLIOI | vision function is disabled, IR is off and ICR is fixed in the day vision mode. |
| | | Bit rate | CBR/VBR two rate control modes, and the output rate range is 128~4096kbps |
| | | Image adjustment | Vertical, horizontal adjustable, OSD display |
| 4 | Audio | Input | Built-in-38dB microphone |
| | | Output | Built-in 8Ω1W speaker |
| | | Sampling frequency/bit width | 8KHz/16bit |
| | | Compression standard/Bit Rate | G711A |
| | Al | Human detection | Human detection, filtering invalid video contents |
| | | Area detection | Free daub, only monitoring the areas concerned by users |
| 5 | | Smart notification sound | Different devices push different sounds, so that you can know exactly which device is triggered |
| | | Intelligent alarm sound | Set different equipment alarm sounds according to different scenarios |
| | | More AI functions (testing) | Pets, vehicles, parcels, etc |
| | | Networking | Use APP to scan the QR code on device to add; Use the device to scan QR code on APP to add |
| 6 | Network | Cat1 China | FDD:B1/B3/B5/B8 |
| | | Cati Cillia | TDD:B34/B38/B39/B40/B41 |
| | | Cat4 Overseas | European/Japanese/American versions |
| 7 | Key/interface Storage | Key 1 | On/Off key |
| | | Reset key | long press to restore factory settings |
| | | External TF card | Support TF card (up to 256GB) |
| | | Cloud storage | Free loop cloud storage |
| 9 | Alarm | Sound light alarm | Sound and light alarm, 11 infrared + 11 white lights, full color night vision |
| | | Alarm detection | Support human detection, PIR detection range: 10 meters |
| 10 | Physical Indicators | Rated voltage | DC5V±5% |
| | | Power supply | Built in 8000mAh battery |
| | | Consumption | Sleep standby 300uA, working: 400MA-1.8A max |
| | | Operating condition | Working temperature: -10 ~ 55°C, working humidity <90% |
| | | Weight | Net weight: 680g |
| | | Size | Camera: 183*164*122mm |
| | | Packing list | Camera*1, manual*1, solar panel*1, solar panel bracket*1 |