


CG621ZS

| Product image | | Features | |
|---|---------------------|---|---|
|  | | ★ Four-lens camera: two fixed lens + two pan&tilt hybrid zoom lens, support ultra long range zoom | |
| | | ★ Two fixed lens support manual horizontal and vertical rotation of 180° | |
| | | ★ F2.0 large aperture, more light inputs, clearer night vision | |
| | | ★ ISP image processing technology, preserving true colors | |
| | | ★ Human detection, real time alerts | |
| No. | Sorts | Type | Parameters |
| 1 | System | Operating system | Linux |
| | | Online visitor | Supports 4 visitors at the same time |
| | | APP | O-KAM Pro |
| 2 | Collection | CPU | Ingenic |
| | | Memory | 512Mb |
| | | Lens | Fixed lens: 4mm+4mm, Pan&tilt lens: 4mm+12mm |
| | | Image sensor | 1/2.7" 1080p progressive scan CMOS sensor |
| | | Minimum | 0.5Lux (color mode), 0.1Lux (b&w mode) |
| | | Sensor performance | Support automatic white balance, automatic gain control and automatic backlight compensation |
| | | Night vision | Black and white night vision, full color night vision |
| 3 | Video | Resolution | 1080P 1920x1080/15FPS/2MP |
| | | Night vision | Black and white night vision, full color night vision |
| | | Compression | H.264 main profile/Motion-JPEG/JPEG |
| | | IR control | IR-CUT, soft photosensitive control |
| | | Bit rate | 128 ~ 4096kbps |
| | | Image adjustment | Brightness, contrast, OSD display |
| 4 | Audio | Input | Built-in -38dB microphone |
| | | Output | Built-in 8Ω1W speaker |
| | | Sampling | 8KHz/16bit |
| | | Compression | G711A |
| 5 | Pan/Tilt | Rotation angle | Pan: 270° tilt: 90° |
| 6 | Network | Network interface | 10Mbps/100Mbps |
| | | Network protocol | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P |
| | | 4G network(China) | FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41 WCDMA:B1/B5/B8 |
| 7 | Storage | External TF card | Supports T-Flash cards (up to 256GB) |
| | | Cloud storage | Support cloud storage, users can purchase according to their needs. |
| 8 | Alarm | Alarm detection | Motion detection, human detection, human framing, human tracking, siren sound, and area detection |
| 9 | Physical Indicators | Rated voltage | DC12V±5% |
| | | Power consumption | Power: 7.8W (0.65A) Maximum power: 11.64W (0.97A) |
| | | Operating condition | Working temperature: -10~55 °C, working humidity<90% |
| | | Weight | Net weight: 650g Gross weight: 1230g |
| | | Camera size | 154x235x185mm |
| | | Packaging box size | 255x210x165mm |
| | | Carton size | 525x435x525mm,12PCS/CARTON |