CS621ZS	
Product image	**Features**
	☆ Four-lens camera: two fixed lens + two pan&tilt hybrid zoom lens, support ultra long range zoom
	☆ Two fixed lens support manual horizontal and vertical rotation of 180°
	☆ F2.0 large aperture, more light inputs, clearer night vision
	☆ ISP image processing technology, preserving true colors
	☆ Human detection, real time alerts

No.	Sorts	Type	Parameters
1	**System**	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	**Collection**	CPU	Ingenic
		Memory	512Mb
		Lens	Fixed lens: 4mm+4mm, Pan&tilt lens: 4mm+12mm
		Image sensor	1/2.7" 1080p progressive scan CMOS sensor
		Minimum	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision, full color night vision
		View angle	4mm: 91°; 12mm: 29°
3	**Video**	Resolution	1080P 1920x1080/15FPS/2MP
		Night vision	Black and white night vision, full color night vision
		Compression	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
4	**Audio**	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling	8KHz/16bit
		Compression	G711A
5	**Pan/Tilt**	Rotation angle	Pan: 270° tilt: 90°
6	**Network**	Network interface	10Mbps/100Mbps, adaptive/RJ45
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
		Wireless security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
7	**Storage**	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
8	**Alarm**	Alarm detection	Motion detection, human detection, human framing, human tracking, siren sound, and area detection
9	**Physical Indicators**	Rated voltage	DC12V±5%
		Power consumption	Power: 6.72W (0.56A) Maximum power: 10.68W (0.89A)
		Operating condition	Working temperature: -10~55 ℃, working humidity<90%
		Weight	Net weight: 638g Gross weight: 1218g
		Camera size	154x235x185mm
		Packaging box size	255x210x165mm
		Carton size	525x435x525mm,12PCS/CARTON