


BG621SR

Product Image		Product features			
		<ul style="list-style-type: none"> ★ Stable 4G connection ★ Remote active wake-up, two-way audio ★ Quick start, start recording within 400ms ★ Intelligent detection of human movement, intelligent alarm push ★ Powered by an 8000mAh battery (optional 20000mAh), low battery reminder ★ Low power system optimization ★ Free cloud storage to save alarm videos ★ Three-channel recordings ★ Dual light source, full color day and night 			
		No.	Sorts	Type	Parameters
		1	System	Operating system	Linux
				Online visitor	Supports 4 visitors at the same time
		2	Collection	APP	O-KAM Pro
				CPU	T23ZX
				Internal storage	1Gbit
Image sensor	GC2083+GC2083+GC2083 1/3CMOS				
Min. Illumination	0.8Lux/F1.4(color mode),0.3Lux/F1.4(B&W mode)				
Lens	Panorama camera: focal length 4mm,1G3P Panorama camera: focal length 4mm, 1G3P				
Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation				
3	Video	Pan&tilt	Adjust the angle of the tracking camera via App, horizontal 270°, vertical 90°;		
		Viewing angle	Manually adjust the angle of the panorama camera, horizontal 180°, vertical 90°		
		Night vision	Full-color night vision, dual light source		
		Compression standard	H.264 /MJPEF/JPEG		
		Multi stream	Main stream: 1080P/12fps Sub stream: 360P/10fps		
		IR control	When the IR night vision function is enabled, IR and ICR are automatically detected; when the IR night vision function is disabled, IR is off and ICR is fixed in the day vision mode.		
		Bit rate	CBR/VBR two rate control modes, and the output rate range is 128~4096kbps		
4	Audio	Image adjustment	Vertical, horizontal adjustable, OSD display		
		Input	Built-in -38dB microphone		
		Output	Built-in 8Q1W speaker		
		Sampling frequency/bit width	8KHz/16bit		
5	AI	Compression standard/Bit	G711A		
		Human detection	Human detection, filtering invalid video contents		
		Area detection	Free daub, only monitoring the areas concerned by users		
		Smart notification sound	Different devices push different sounds, so that you can know exactly which device is triggered		
		Intelligent alarm sound	Set different equipment alarm sounds according to different scenarios		
6	Network	More AI functions (testing)	Pets, vehicles, parcels, etc		
		Network connection	Use APP to scan the QR code on device to add; Use the device to scan QR code on APP to add		
		Cat1 China	FDD:B1/B3/B5/B8		
		Cat4 Overseas	TDD: B34/B38/B39/B40/B41 European/Japanese/American versions		
7	Key/interface	Key 1	On/Off key		
		Reset key	Long press to restore factory settings		
8	Storage	External TF card	Support TF card (up to 256GB)		
		Cloud storage	Free cloud storage		
9	Alarm	Sound light alarm	Sound and light alarm		
		Alarm detection	Support human detection, PIR detection range: 10 meters		
10	Physical Indicators	Rated voltage	DC5V/2.5A±5%		
		Power supply	Built-in 8000mAh battery, optional 20000mAh		
		Consumption	Sleep standby 300uA, working: 350mA-1.8A max		
		Operating condition	Working temperature: -10 ~ 55°C, working humidity <90%		
		Weight	Net weight: 818g		
		Size	183*235*180mm		
		Packing list	Camera*1, TYPE-C*1, manual*1, solar panel*1, solar panel bracket*1		