


C4DR			
Product Image		Features	
		★F2.0 large aperture, more light inputs, clearer night vision	
		★WiFi connection	
		★Active defense; the device triggers sound-light alarm upon intrusion	
		★Support remote monitoring via mobile and PC clients, view live footage anytime anywhere	
		★ISP image processing technology, preserving true colors	
		★Dual-core light board, 24/7 full-color	
		★Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating System	Linux
		Online Visitor	Supports 4 visitors at the same time
		APP	VStarcam Ultra
2	Collection	Processor	Tsingmicro TX5110CV206
		Memory	512Mb
		Lens	3.6mm
		Image Sensor	1/3.3" GC20C3 1080p progressive scan CMOS sensor
		Min. Illumination	0.5Lux (Color), 0.1Lux (B/W)
		Sensor Performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night Vision	Color Night Vision, Infrared Night Vision
Field of View	79 ° diagonal		
3	Video	Resolution	1080P 1920x1080/15FPS/2MP; 1296P 2304x1296/15FPS/3MP (interpolation)
		Night Vision Range	5-10m
		Compression Standard	H.264 main profile/Motion-JPEG/JPEG
		IR Control	IR-CUT, soft photosensitive control
		Bit Rate	128 ~ 4096kbps
Image Adjustment	Brightness, contrast, OSD display		
4	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling Frequency / Bit Depth	8KHz/16bit
		Compression Standard/Bit Rate	G711A
5	PTZ	Movement Range	Pan:310° Tilt: 65°
6	Network	Network Interface	N/A
		Network Protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless Network	IEEE802.11b/g/n
		Wireless Frequency	2.4G
Wireless Security	64/128-bit WEP/WPA-PSK/WPA2-PSK		
7	Storage	External TF Card	Support TF card (up to 256GB)
		Cloud Storage	Cloud storage supported (subscription required)
8	Alarm	Alarm Detection	Motion detection, human detection, human framing, human tracking, and area detection
9	Physical Indicators	Rated Voltage	DC5V±5%
		Power Consumption	Power: 1.6W (0.32A) Max. Power: 2.75W (0.55A)
		Operating Condition	Temperature: -10 ~ 45°C; Humidity: < 90%
		Weight	Net weight: 138g; Gross weight: 338g
		Product Dimension	79x79x108mm
		Package Dimension	90x90x185mm
		Carton Dimension	470x470x395mm
		QTY/CTN	50PCS
Package Contents	Camera ×1, Bracket×1, Power Adapter ×1, Power Cable ×1, User Manual ×1, Screw Kit ×1		