


CG622DR			
Product Image		Features	
		★Two cameras in one, dual views with no blind spots	
		★Dual-core light panel, color night vision	
		★ISP image processing technology, preserving true colors	
		★Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic
		Memory	512Mb
		Lens	4mm
		Image sensor	1/2.7" 1080p progressive scan CMOS sensor
		Min. Illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision, full-color night vision
3	Video	Viewing angle	91°
		Resolution	1080P 1920x1080/15FPS/2MP ; 1296P 2304x1296/15FPS/3MP(Interpolation)
		Night vision	Black and white night vision, full-color night vision
		Compression	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
4	Audio	Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
		Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling	8KHz/16bit
5	Pan/Tilt	Rotation angle	Pan: 270° Tilt: 90°
6	Network	4G network(China)	FDD:B1/B3/B8 TDD:B34/B38/B39/B40
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
8	Alarm	Alarm detection	Motion detection, human detection, human framing, human tracking, siren alarm, and area detection
9	Physical Indicators	Rated voltage	DC12V±5%
		Power consumption	Power: 6.96W (0.58A) Maximum power: 10.56W (0.88A)
		Operating condition	Working temperature: -10~55 °C, working humidity<90%
		Weight	Net weight: 409g Gross weight: 570g
		Camera size	146x116x170mm
		Packaging box size	205x160x140mm
		Carton size	580x425x345mm,16PCS/Carton