


CS4

Product Image		Features	
		★ F2.0 large aperture, more light intake, clearer night vision	
		★ Dual light source, full color day and night	
		★ ISP image processing technology, preserving true colors	
		★ Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Tsingmicro TX5110CV206
		Memory	512Mb
		Lens	4mm
		Image sensor	1/3.3" GC20C3 1080p progressive scan CMOS sensor
		Min. Illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision, full-color night vision
		Viewing angle	79°
3	Video	Resolution	1080P 1920x1080/15FPS/2MP ; 1296P 2304x1296/15FPS/3MP (interpolation)
		Night vision	5-10meters
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
4	Audio	Image adjustment	Brightness, contrast, OSD display
		Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
5	Pan/Tilt	Rotation angle	Pan:310° Tilt: 65°
6	Network	Network interface	N/A
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
7	Storage	Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK
		External TF card	Supports T-Flash cards (up to 256GB)
8	Alarm	Cloud storage	Support cloud storage (sold separately)
		Alarm detection	Motion detection, human detection, human framing,human tracking, and area detection
9	Physical Indicators	Rated voltage	DC5V±5%
		Power consumption	Power: 1.6W (0.32A) Maximum power: 2.75W (0.55A)
		Operating condition	Working temperature: -10 ~ 45°C, working humidity <90%
		Weight	Net weight: 138g; Gross weight: 338g
		Camera size	79x79x116mm
		Packaging box size	90x90x173mm
		Carton size	470x470x395mm,50PCS/CARTON
Packaging List		Camera × 1, Mount × 1, Power Cord × 1, User Manual × 1	