


TG4DR

| Product Image | | Features | |
|---|---------------------|---|--|
|  | | ★ Dual lens ensuring coverage with no blind spots, two cameras in one | |
| | | ★ Dual-core light board, full color day and night | |
| | | ★ ISP image processing technology, preserving true colors | |
| | | ★ Dual channel recording | |
| | | ★ Human detection, real time alerts | |
| No. | Sorts | Type | Parameters |
| 1 | System | Operating system | Linux |
| | | Online visitor | Supports 4 visitors at the same time |
| | | APP | O-KAM Pro |
| 2 | Collection | CPU | Ingenic |
| | | Memory | 512Mb |
| | | Lens | 4mm |
| | | Image sensor | 1/2.7" 1080p progressive scan CMOS sensor |
| | | Min. Illumination | 0.5Lux (color mode), 0.1Lux (b&w mode) |
| | | Sensor performance | Support automatic white balance, automatic gain control and automatic backlight compensation |
| | | Night vision | Black and white night vision, full-color night vision |
| Viewing angle | Diagonal: 91° | | |
| 3 | Video | Resolution | 1080P 1920x1080/15FPS/2MP; 1296P 2304x1296/15FPS/3MP (interpolation) |
| | | Night vision | Black and white night vision, full-color night vision |
| | | Compression standard | H.264 main profile/Motion-JPEG/JPEG |
| | | IR control | IR-CUT, soft photosensitive control |
| | | Bit rate | 128 ~ 4096kbps |
| | | Image adjustment | Brightness, contrast, OSD display |
| 4 | Audio | Input | Built-in -38dB microphone |
| | | Output | Built-in 8Ω1W speaker |
| | | Sampling frequency/bit width | 8KHz/16bit |
| | | Compression standard/Bit Rate | G711A |
| 5 | Pan/Tilt | Rotation angle | Pan:310° Tilt: 65° |
| 6 | Network | 4G network (China) | FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41 WCDMA:B1/B5/B8 |
| 7 | Storage | External TF card | Supports T-Flash cards (up to 256GB) |
| | | Cloud storage | Support cloud storage, users can purchase according to their needs. |
| 8 | Alarm | Alarm detection | Motion detection, human detection, human framing, human tracking, and area detection |
| 9 | Physical Indicators | Rated voltage | DC5V±5% |
| | | Power consumption | Power: 2.75W (0.57A) Maximum power: 6.1W (1.22A) |
| | | Operating condition | Working temperature: -10 ~ 45°C, working humidity <90% |
| | | Weight | Net weight: 172g; Gross weight: 372g |
| | | Camera size | 79x79x116mm |
| | | Packaging box size | 90x90x173mm |
| | | Carton size | 470x470x370mm, 50PCS/Carton |