

CB622DR			
Product Image		Product features	
		<ul style="list-style-type: none"> ★ Wireless connection ★ Remote active wake-up, two-way voice intercom ★ 400ms quick start recording ★ Intelligent detection of human movement, intelligent alarm push ★ 6000mAh battery powered, low battery warning ★ Low power system optimization ★ Support cloud storage ★ Dual channel recording ★ Dual lens linkage, auto zoom ★ Dual light source, color night vision 	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	T23ZN
		Internal storage	512MB
		Image sensor	GC2083+GC2083
		Min. Illumination	0.8Lux/F1.4(color mode),0.3Lux/F1.4(B&W mode)
		Lens	Panorama camera: focal length 4mm,1G3P ; Tracking camera: focal length 4mm, 1G3P
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
3	Video	Pan&tilt	Horizontal 260°, vertical 90°
		Viewing angle	Panorama camera, diagonal 100°, tracking camera, diagonal 60°
		Night vision	Color night vision, dual light sources, 7pcs dual-color dual light source lights
		Compression standard	MJPEF/JPEG
		Multi stream	Main stream: 1080P/15fps Sub stream: 360P/15fps
4	Audio	IR control	When the IR night vision function is enabled, IR and ICR are automatically detected; when the IR night vision function is disabled, IR is off and ICR is fixed in the day vision mode.
		Bit rate	CBR/VBR two rate control modes, and the output rate range is 128~4096kbps
		Image adjustment	Vertical, horizontal adjustable, OSD display
		Input	Built-in-38dB microphone
5	AI	Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
		Human detection	Human detection, filtering invalid video contents
		Area detection	Free dab, only monitoring the areas concerned by users
6	Network	Smart notification sound	Different devices push different sounds, so that you can know exactly which device is triggered
		Intelligent alarm sound	Set different equipment alarm sounds according to different scenarios
		More AI functions (testing)	Pets, vehicles, parcels, etc
		Networking	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P,IPV4
		Network Protocol	IEEE802.11b/g/n
		wireless network	2.4G,5.1G,5.2G,5.4G or 5.8G
7	Key/interface	Wireless frequency	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
		Wireless secure encryption	AP hotspot network configuration, Scan QR code to add device, Bluetooth network configuration
8	Storage	Key 1	On/Off key
		Reset key	long press to restore factory settings
9	Alarm	External TF card	Support TF card (up to 256GB)
		Cloud storage	Support
10	Physical Indicators	Sound light alarm	Sound and light alarm
		Alarm detection	Support human detection, PIR detection range: 10 meters
		Rated voltage	DC5V±5%
		Power supply	6000mAh battery power supply
		Consumption	Sleep standby 300uA, working: 230mA-1.5A max
		Operating condition	Working temperature: -10 ~ 55°C, working humidity <90%
		Weight	Net weight: 580g; Gross weight: 1150g
		Product size	115*162*167mm
		Packing list	Camera*1, manual*1, solar panel*1, solar panel bracket*1