CB622			
Product Image		duct Image	Product features
		•	★ WiFi connection, dual band WiFi 2.4/5G
		1	★ Remote active wake-up, two-way voice intercom
			★ Quick start, start recording within 400ms
			★ Intelligent detection of human movement, intelligent alarm push
			★ 6000mAh battery, low battery warning
•			★ Low power system optimization
			★ Free cloud storage
			★ Dual light source, full color day and night
			★Low power and corded power compatible design
No.	Sorts	Туре	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	T23ZN
		Memory	512MB
		Image sensor	GC2083
		Min. Illumination	0.8Lux/F1.4(color mode),0.3Lux/F1.4(B&W mode)
		Lens	Focal length 4mm, 1G3P
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Pan&tilt	Horizontal 270°, vertical 90°
		Viewing angle	D100°
3	Video	Night vision	Color night vision, dual light sources, 3pcs dual-color dual light source lights
		Compression standard Multi stream	MJPEF/JPEG  Maintergram 1000P/15fee, cub stream 260P/15fee
		Walti Stream	Mainstream:1080P/15fps, sub stream:360P/15fps  When the IR night vision function is enabled, IR and ICR are automatically detected; when the IR
		IR control	night vision function is disabled, IR is off and ICR is fixed in the day vision mode.
		Bit rate	CBR/VBR two rate control modes, and the output rate range is 128~4096kbps
		Image adjustment	Vertical, horizontal adjustable, OSD display
	Audio	Input	Built-in-38dB microphone
		Output	Built-in 8Ω1W speaker
4		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
5	Al	Human detection	Human detection, filtering invalid video contents
		Area detection	Free daub, only monitoring the areas concerned by users
		Smart notification sound	Different devices push different sounds, so that you can know exactly which device is triggered
		Intelligent alarm sound	Set different equipment alarm sounds according to different scenarios
		More Al functions (testing)	Pets, vehicles, parcels, etc
7	Network Key/interface	Network protocol Wireless network	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P,IPV4 IEEE802.11b/g/n
		Wireless frequency	2.4~2.4835GHz
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK
		Connection	AP hotspot network configuration, QR code network configuration, bluetooth network configuration
		Key 1	On/Off key
		Reset key	long press to restore factory settings
8	Storage Alarm	External TF card	Support TF card (up to 256GB)
		Cloud storage	Free loop cloud storage
		Sound light alarm	Sound and light alarm
		Alarm detection	Support human detection, PIR detection range: 10 meters
10	Physical Indicators	Rated voltage	DC5V±5%
		Power supply	Built in 6000mAh battery
		Consumption	Sleep standby 300uA, working: 230MA-1.5A max
		Operating condition	Working temperature: $-10 \sim 55$ °C, working humidity < 90%
		Weight	Net weight: 560g; Gross weight: about 1.13KG
		Product size	115*162*167mm
	Packing list		Camera*1, manual*1, solar panel*1, solar panel bracket*1
Ì			