

CSSH			
Product Image			Features
			★ F2.0 large aperture, more light inputs, clearer night vision
			★ Dual-core light board, full color day and night
			★ 2K super HD
			★ Full-duplex Two-Way Audio Intercom
			★ One tap wireless connect
			★ ISP image processing technology, preserving true colors
			★ Human detection, real time alerts
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	VStarcam Ultra
2	Collection	Processor	Hi608
		Memory	512Mb
		Lens	3.6mm
		Image sensor	1/3.3" 1080p progressive scan CMOS sensor
		Min. Illumination	0.5Lux (Color), 0.1Lux (B/W)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Color Night Vision, Infrared Night Vision
3	Video	Field of View	79° diagonal
		Resolution	1080P 1920x1080/15FPS/2MP; 1296P 2304x1296/15FPS/3MP(Interpolation)
		Night vision range	5-10m
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
4	Audio	Image adjustment	Image flip, OSD display
		Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency / Bit depth	8KHz/16bit
5	PTZ	Compression standard/Bit rate	G711A
		Movement range	Pan: 240° Tilt: No supported
6	Network	Network interface	10Mbps/100Mbps, adaptive/RJ45
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
7	Storage	Wireless security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
		External TF card	Support TF card (up to 256GB)
		Cloud storage	Cloud storage supported (subscription required)
8	Alarm	Alarm detection	Motion detection, human detection, human framing, area detection, human tracking
9	Physical Indicators	Rated voltage	DC12V±5%
		Power consumption	Power: 4.32W (0.36A) Maximum power: 7.8W (0.65A)
		Operating condition	Temperature: -10 ~ 45°C; Humidity: < 90%
		Weight	Net weight: 237g; Gross weight: 437g
		Product Dimension	80x65x139mm
		Package Dimension	175x98x130mm
		Carton Dimension	540x510x285mm
		QTY/CTN	30PCS
		Package Contents	Camera ×1, Bracket ×1, Power Supply ×1, Manual ×1, Screw Pack ×1