No. 1 2 3 4	Pro	Aduct Image  Type  Operating system  Online visitor  APP  CPU  Memory Lens Image sensor  Minimum illumination  Sensor performance	Features         ★ F2.0 large aperture, more light inputs, clearer night vision         ★ Dual-core light board, full color day and night         ★ ISP image processing technology, preserving true colors         ★ Human detection, real time alerts         Parameters         Linux         Supports 4 visitors at the same time         O-KAM Pro         Ingenic         512Mb         4mm         1/2.7" 1080p progressive scan CMOS sensor         0.5Lux (color mode), 0.1Lux (b&w mode)
2 3	System	Operating system Online visitor APP CPU Memory Lens Image sensor Minimum illumination	<ul> <li>★ Dual-core light board, full color day and night</li> <li>★ ISP image processing technology, preserving true colors</li> <li>★ Human detection, real time alerts</li> <li>Parameters</li> <li>Linux</li> <li>Supports 4 visitors at the same time</li> <li>O-KAM Pro</li> <li>Ingenic</li> <li>512Mb</li> <li>4mm</li> <li>1/2.7" 1080p progressive scan CMOS sensor</li> </ul>
2 3	System	Operating system Online visitor APP CPU Memory Lens Image sensor Minimum illumination	<ul> <li>ISP image processing technology, preserving true colors</li> <li>Human detection, real time alerts</li> <li>Parameters</li> <li>Linux</li> <li>Supports 4 visitors at the same time</li> <li>O-KAM Pro</li> <li>Ingenic</li> <li>512Mb</li> <li>4mm</li> <li>1/2.7" 1080p progressive scan CMOS sensor</li> </ul>
2 3	System	Operating system Online visitor APP CPU Memory Lens Image sensor Minimum illumination	Human detection, real time alerts          Parameters         Linux         Supports 4 visitors at the same time         O-KAM Pro         Ingenic         512Mb         4mm         1/2.7" 1080p progressive scan CMOS sensor
2 3	System	Operating system Online visitor APP CPU Memory Lens Image sensor Minimum illumination	Parameters         Linux         Supports 4 visitors at the same time         O-KAM Pro         Ingenic         512Mb         4mm         1/2.7" 1080p progressive scan CMOS sensor
2 3	System	Operating system Online visitor APP CPU Memory Lens Image sensor Minimum illumination	Linux Supports 4 visitors at the same time O-KAM Pro Ingenic 512Mb 4mm 1/2.7" 1080p progressive scan CMOS sensor
2		Online visitor APP CPU Memory Lens Image sensor Minimum illumination	Supports 4 visitors at the same time O-KAM Pro Ingenic 512Mb 4mm 1/2.7" 1080p progressive scan CMOS sensor
2		APP CPU Memory Lens Image sensor Minimum illumination	O-KAM Pro Ingenic 512Mb 4mm 1/2.7" 1080p progressive scan CMOS sensor
3	Collection	CPU Memory Lens Image sensor Minimum illumination	Ingenic 512Mb 4mm 1/2.7" 1080p progressive scan CMOS sensor
3	Collection	Memory Lens Image sensor Minimum illumination	512Mb 4mm 1/2.7" 1080p progressive scan CMOS sensor
3	Collection	Lens Image sensor Minimum illumination	4mm 1/2.7" 1080p progressive scan CMOS sensor
3	Collection	Image sensor Minimum illumination	1/2.7" 1080p progressive scan CMOS sensor
3	Collection	Minimum illumination	
3	Collection		0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	
			Support automatic white balance, automatic gain control and automatic backlight
		Nightvision	compensation
		Night vision	Black and white night vision, full-color night vision
		Viewing angle	Diagonal : 91 °
	Video	Resolution	1080P 1920x1080/15FPS/2MP; 1296P 2304x1296/15FPS/3MP(Interpolation)
		Night vision	Black and white night vision, full-color night vision
4		Compression standard	H.264 main profile/Motion-JPEG/JPEG
4		IR control	IR-CUT, soft photosensitive control
4		Bit rate	128 ~ 4096kbps
4		Image adjustment	Brightness, contrast, OSD display
4		Input	Built-in -38dB microphone
-	Audio	Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
5	PTZ	Rotation angle	Horizontal: 240° Vertical: /
		Network interface	10Mbps/100Mbps, adaptive/RJ45
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
6	Network	Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)
1	Storage	Cloud storage	Support cloud storage, users can purchase according to their needs.
8	Alarm	Alarm detection	Motion detection, human detection, human framing, area detection, human tracking
	Physical Indicators	Rated voltage	DC12V±5%
		Power consumption	Power: 4.32W (0.36A) Maximum power: 7.8W (0.65A)
		Operating condition	Working temperature: -10~45 °C, working humidity<90%
9 PI			Net weight: 237g; Gross weight: 437g
		Camera size	80x65x139mm
		Packaging box size	175x98x130mm
		Carton size	540x510x285mm,30PCS/CARTON