


CS2DR			
Product Image		Features	
		★Dual lens dual view leaves no blind spots	
		★F2.0 large aperture, more light inputs, clearer night vision	
		★ISP image processing technology, preserving true colors	
		★Dual channel real-time recording, guarding multiple directions	
		★Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic
		Memory	512Mb
		Lens	4mm
		Image sensor	1/2.7" 1080p progressive scan CMOS sensor
		Minimum illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision, full-color night vision
3	Video	Viewing angle	Diagonal : 91 °
		Resolution	1080P 1920x1080/15FPS/2MP; 1296P 2304x1296/15FPS/3MP
		Night vision	Black and white night vision, full-color night vision
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
4	Audio	Image adjustment	Brightness, contrast, OSD display
		Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling	8KHz/16bit
		Compression	G711A
5	Pan&Tilt	Angle	Pan： 340° Tilt： 90°
6	Network	Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
		Wireless security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
8	Alarm	Alarm detection	Motion detection, human detection, human framing, area detection, human tracking
9	Physical Indicators	Rated voltage	DC5V±5%
		Power consumption	Power: 2.6W (0.52A) Maximum power: 3.65W (0.73A)
		Operating condition	Working temperature: -10~45 °C, working humidity<90%
		Weight	Net weight: 319g Gross weight: 620g
		Camera size	116x114x114mm
		Packaging box size	124x120x178mm
		Carton size	640x620x380mm, 20pcs/carton