CS49LM

Product Image	Features
	☆Dual-core light panel, color night vision
	☆Smoke detection, combustible gas detection, precise detection, remote alarm
	☆ISP image processing technology, preserving true colors
	☆Human detection, real time alerts

No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic
		Memory	512Mb
		Lens	4mm
		Image sensor	1/3" 1080p progressive scan CMOS sensor
		Min. Illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision, full-color night vision
		Viewing angle	Diagonal: 91°
3	Video	Resolution	1080P, 1920x1080/15FPS/2MP；1296P, 2304x1296/15FPS/3MP
		Night vision	Black and white night vision, full-color night vision
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128～4096kbps
		Image adjustment	Brightness, contrast, OSD display
4	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit	8KHz/16bit
		Compression standard/Bit	G711A
5	Pan/Tilt	Rotation angle	Diagonal: 91°
6	Network	Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
		Wireless security	64/128-bit WEP/WPA-PSK/WPA2-PSK
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
8	Alarm	Alarm detection	Support smoke detection, combustible gas detection, motion detection, human detection, human framing, human tracking, and area detection
9	Physical Indicators	Rated voltage	5V±5%
		Power consumption	Power: 3.5W (infrared light on) Maximum power: 5.5W
		Operating condition	Working temperature: -10~55 ℃, working humidity<90%
		Weight	Net weight: 195g; Gross weight: 365g
		Camera size	80x90x110mm'
		Packaging box size	90x90x185mm （L*W*H)
		Carton size	470x470x395mm, 50pcs/Carton
		Packaging list	Camera, screw package, manual