


BG621ZS			
Product Image		Product features	
		★Stable 4G connection	
		★Remote active wake-up, two-way audio	
		★Quick start, start recording within 400ms	
		★Intelligent detection of human movement, intelligent alarm push	
		★ Powered by an 8000mAh battery (optional 20000mAh), low battery reminder	
		★ Low power system optimization	
		★Free cloud storage to save alarm videos	
		★Three-channel recordings	
		★The tracking camera can switch between long and short focus	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	T23
		Internal storage	1Gbit
		Image sensor	OV 02N10 1/3CMOS
		Min. Illumination	0.8Lux/F1.4(color mode), 0.3Lux/F1.4(B&W mode)
		Lens	Fixed camera: focal length 4mm+4mm, 1G3P tracking camera: focal length 4mm(1G3P )+12mm (1G2P)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Pan&tilt	Tracking camera adjust angle via the App, pan 270° tilt 90°, fixed camera adjust angle manually: horizontal180°, vertical 90°
		Viewing angle	D100°
3	Video	Night vision	Full-color night vision, dual light source
		Compression	H.264 /MJPEF/JPEG
		Multi stream	Main stream: 1080P/12fps Sub stream: 360P/10fps
		IR control	When the IR night vision function is enabled, IR and ICR are automatically detected; when the IR night vision function is disabled, IR is off and ICR is fixed in the day vision mode.
		Bit rate	CBR/VBR two rate control modes, and the output rate range is 128~4096kbps
		Image adjustment	Vertical, horizontal adjustable, OSD display
4	Audio	Input	Built-in-38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling	8KHz/16bit
		Compression	G711A
5	AI	Human detection	Human detection, filtering invalid video contents
		Area detection	Free daub, only monitoring the areas concerned by users
		Smart notification	Different devices push different sounds, so that you can know exactly which device is triggered
		Intelligent alarm	Set different equipment alarm sounds according to different scenarios
		More AI functions	Pets, vehicles, parcels, etc
6	Network	Network connection	Use APP to scan the QR code on device to add; Use the device to scan QR code on APP to add
		Cat1 China	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41
		Cat4 Overseas	European version/Japanese version/American version/Australian version
7	Key/interface	Key 1	On/Off key
		Reset key	Long press to restore factory settings
8	Storage	External TF card	Support TF card (up to 256GB)
		Cloud storage	Free cloud storage
9	Alarm	Sound light alarm	Sound and light alarm
		Alarm detection	Support human detection, PIR detection range: 10 meters
		Rated voltage	DC5V/2.5A±5%
10	Physical Indicators	Power supply	Built-in 8000mAh battery, optional 20000mAh
		Consumption	Sleep standby 300uA, working: 350mA-1.8A max
		Operating condition	Working temperature: -10 ~ 55°C, working humidity <90%
		Weight	Net weight: 818g Gross weight: TBD
		Size	183*235*180mm
		Packing list	Camera*1, TYPE-C*1, manual*1, solar panel*1, solar panel bracket*1