Product Picture	
*Remote active wake-up, two-way voice intercom *Quick start, start recording within 400ms *Intelligent detection of human movement, intelligent alarm push *5200mAh battery power supply, low power warning *Dual light source, full color day and night, 56 fill lights *Free cloud storage to save alarm videos *Support external 5W solar panels, continuously transmit power, and the equipmen *Smart Al No. Category Type Parameter Operating system Embedded Linux Online visitor Supports 4 visitors at the same time APP O-KAM Pro Processor T23 Memory 512Mb Image sensor GC2083, 200W,1/3CMOS Minimum illumination 0.8Lux/F1.4(Color mode), 0.3Lux/F1.4 (B&W mode) Lens Standard lens diameter 14mm Sensor performance Support Automatic white balance, Automatic gain control, Automatic backlight comp Viewing angle D110° Night vision Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights, irradiation distance: 5~8m Compression H.264 /MJPEF/JPEG	
*Remote active wake-up, two-way voice intercom *Quick start, start recording within 400ms *Intelligent detection of human movement, intelligent alarm push *5200mAh battery power supply, low power warning *Dual light source, full color day and night, 56 fill lights *Free cloud storage to save alarm videos *Support external 5W solar panels, continuously transmit power, and the equipmen *Smart Al No. Category Type Parameter Operating system Embedded Linux Online visitor Supports 4 visitors at the same time APP O-KAM Pro Processor T23 Memory 512Mb Image sensor GC2083, 200W,1/3CMOS Minimum illumination 0.8Lux/F1.4(Color mode), 0.3Lux/F1.4 (B&W mode) Lens Standard lens diameter 14mm Sensor performance Support Automatic white balance, Automatic gain control, Automatic backlight comp Viewing angle D110° Night vision Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights, irradiation distance: 5~8m Compression H.264 /MJPEF/JPEG	
★ Quick start, start recording within 400ms ★ Intelligent detection of human movement, intelligent alarm push ★ 5200mAh battery power supply, low power warning ★ Dual light source, full color day and night, 56 fill lights ★ Free cloud storage to save alarm videos ★ Support external 5W solar panels, continuously transmit power, and the equipmen ★ Smart Al	
* Intelligent detection of human movement, intelligent alarm push *5200mAh battery power supply, low power warning *Dual light source, full color day and night, 56 fill lights *Free cloud storage to save alarm videos *Support external 5W solar panels, continuously transmit power, and the equipmen *Smart Al	
*5200mAh battery power supply, low power warning *Dual light source, full color day and night, 56 fill lights *Free cloud storage to save alarm videos *Support external 5W solar panels, continuously transmit power, and the equipmen *Smart Al No. Category Type Parameter Operating system Embedded Linux Online visitor Supports 4 visitors at the same time APP O-KAM Pro Processor T23 Memory 512Mb Image sensor GC2083, 200W,1/3CMOS Image sensor GC2083, 200W,1/3CMOS Minimum illumination 0.8Lux/F1.4(Color mode), 0.3Lux/F1.4 (B&W mode) Lens Standard lens diameter 14mm Sensor performance Support Automatic white balance, Automatic gain control, Automatic backlight comprised by Support Support Automatic white balance, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights, irradiation distance: 5~8m Compression H.264 /MJPEF/JPEG	
*Dual light source, full color day and night, 56 fill lights ★ Free cloud storage to save alarm videos ★ Support external 5W solar panels, continuously transmit power, and the equipmen ★ Smart Al No. Category Type Parameter Operating system Embedded Linux Online visitor Supports 4 visitors at the same time APP O-KAM Pro Processor T23 Memory 512Mb Image sensor GC2083, 200W,1/3CMOS Image sensor GC2083, 200W,1/3CMOS Lens Standard lens diameter 14mm Sensor performance Support Automatic white balance, Automatic gain control, Automatic backlight comproviewing angle D110° Night vision Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights, irradiation distance: 5~8m Compression H.264 / MJPEF/JPEG	
* Free cloud storage to save alarm videos * Support external 5W solar panels, continuously transmit power, and the equipmen * Smart AI No. Category Type Parameter Operating system Embedded Linux Online visitor Supports 4 visitors at the same time APP O-KAM Pro Processor T23 Memory 512Mb Image sensor GC2083, 200W,1/3CMOS Image sensor GC2083, 200W,1/3CMOS Lens Standard lens diameter 14mm Sensor performance Support Automatic white balance, Automatic gain control, Automatic backlight comp Viewing angle D110° Night vision Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights, irradiation distance: 5~8m Compression H.264 / MJPEF/JPEG	
Support external 5W solar panels, continuously transmit power, and the equipment Smart Al	
No. Category Type Parameter Operating system Embedded Linux Online visitor Supports 4 visitors at the same time APP O-KAM Pro Processor T23 Memory 512Mb Image sensor GC2083, 200W,1/3CMOS Minimum illumination 0.8Lux/F1.4(Color mode), 0.3Lux/F1.4 (B&W mode) Lens Standard lens diameter 14mm Sensor performance Support Automatic white balance, Automatic gain control, Automatic backlight compoviewing angle D110° Night vision Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights, irradiation distance: 5~8m Compression H.264 /MJPEF/JPEG	
No. Category Type Parameter Operating system Embedded Linux Online visitor Supports 4 visitors at the same time APP O-KAM Pro Processor T23 Memory 512Mb Image sensor GC2083, 200W,1/3CMOS Minimum illumination 0.8Lux/F1.4(Color mode), 0.3Lux/F1.4 (B&W mode) Lens Standard lens diameter 14mm Sensor performance Viewing angle D110° Night vision Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights, irradiation distance: 5~8m Compression H.264 /MJPEF/JPEG	it won't not powered
1 System Operating system Embedded Linux Online visitor Supports 4 visitors at the same time APP O-KAM Pro Processor T23 Memory 512Mb Image sensor GC2083, 200W,1/3CMOS Minimum illumination 0.8Lux/F1.4(Color mode), 0.3Lux/F1.4 (B&W mode) Lens Standard lens diameter 14mm Sensor performance Support Automatic white balance, Automatic gain control, Automatic backlight comprised by Signal Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light So white lights, irradiation distance: 5~8m Compression H.264 / MJPEF/JPEG	
1 System Online visitor Supports 4 visitors at the same time APP O-KAM Pro Processor T23 Memory 512Mb Image sensor GC2083, 200W,1/3CMOS Minimum illumination 0.8Lux/F1.4(Color mode), 0.3Lux/F1.4 (B&W mode) Lens Standard lens diameter 14mm Sensor performance Support Automatic white balance, Automatic gain control, Automatic backlight compoviewing angle D110° Night vision Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights, irradiation distance: 5~8m Compression H.264 /MJPEF/JPEG	
APP O-KAM Pro Processor T23 Memory 512Mb Image sensor GC2083, 200W,1/3CMOS Collection Minimum illumination 0.8Lux/F1.4(Color mode), 0.3Lux/F1.4 (B&W mode) Lens Standard lens diameter 14mm Sensor performance Viewing angle D110° Night vision Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights. irradiation distance: 5~8m Compression H.264 /MJPEF/JPEG	
Processor T23 Memory 512Mb Image sensor GC2083, 200W,1/3CMOS Minimum illumination 0.8Lux/F1.4(Color mode), 0.3Lux/F1.4 (B&W mode) Lens Standard lens diameter 14mm Sensor performance Support Automatic white balance, Automatic gain control, Automatic backlight compound of Viewing angle D110° Night vision Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights, irradiation distance: 5~8m Compression H.264 /MJPEF/JPEG	
2 Collection Memory 512Mb Image sensor GC2083, 200W,1/3CMOS Minimum illumination 0.8Lux/F1.4(Color mode), 0.3Lux/F1.4 (B&W mode) Lens Standard lens diameter 14mm Sensor performance Support Automatic white balance, Automatic gain control, Automatic backlight compound of Viewing angle D110° Night vision Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights, irradiation distance: 5~8m Compression H.264 /MJPEF/JPEG	
Collection Minimum illumination 0.8Lux/F1.4(Color mode), 0.3Lux/F1.4 (B&W mode) Lens Standard lens diameter 14mm Sensor performance Support Automatic white balance, Automatic gain control, Automatic backlight composition Viewing angle D110° Night vision Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights, irradiation distance: 5~8m Compression H.264 / MJPEF/JPEG	
Lens Standard lens diameter 14mm Sensor performance Support Automatic white balance, Automatic gain control, Automatic backlight composition Viewing angle D110° Night vision Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights, irradiation distance: 5~8m Compression H.264 / MJPEF/JPEG	
Lens Standard lens diameter 14mm Sensor performance Support Automatic white balance, Automatic gain control, Automatic backlight composition Viewing angle D110° Night vision Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights, irradiation distance: 5~8m Compression H.264 / MJPEF/JPEG	
Viewing angle D110° Night vision Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights, irradiation distance: 5~8m Compression H.264 / MJPEF/JPEG	
Night vision Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED light 50 white lights, irradiation distance: 5~8m Compression H.264 / MJPEF/JPEG	ensation
50 white lights, irradiation distance: 5~8m Compression H.264 / MJPEF/JPEG	
Compression H.264 / MJPEF/JPEG	s, full color night vision,
COMMICSION	
Main stroom 1206B/1Efns Sub stroom 260B/1Efns	
3 Video Multi-stream Main stream: 1296P/15fps Sub stream: 360P/15fps	
IR control IR night vision enables; IR, ICR automatic detection; IR OFF night vision function disab	led/ IR always OFF, ICR
is fixed in the day vision mode	
Bit rate CBR / VBR two rate control modes, and the output rate range is 128 ~ 4096kbps	
Image adjustment Brightness, contrast, OSD display	
Input Built-in—38dB microphone	
4 Audio Output Built-in 80.1W speaker	
Sampling 8KHz/16bit Compression G711A	
Compression G711A Humanoid detection Humanoid detection, filtering invalid video content	
, ,	
. , , ,	And a second
5 AI Smart notification Different devices push different sounds, so that you can know exactly which device is	triggered
Intelligent alarm Set different equipment alarm sounds according to different scenarios	
More Al functions Pets, vehicles, parcels, etc	
Network protocol TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P,IPV4	
Wireless network IEEE802.11b/g/n/ax	
6 Network Wireless frequency 2.4G	
Wireless security 64/128-bit WEP/WPA-PSK/WPA3 data encryption	
encryption Wireless connection AP hotspot network configuration, QR code network configuration, bluetooth network	rk configuration
Key1 Power ON/OFF	K Configuration
7 Key Reset key Long Press to restore the factory settings	
External TE card Support TE card (up to 256GR)	
8 Storage Cloud storage Free cloud storage	
9 Alarm Alarm detection Support PIR human detection	
Rated voltage DC5V±5%	
Power supply 5200mAh battery, 2*21700, supports external 5V solar panel	
Power Sleep current 260uA, working: 230-1.2mA	
10 Physical Indicators Power consumption Temperature: -10 ~ 55°C; Humidity: < 90%	
Operating condition Net weight: 264g Gross weight: 400g	
Weight Camera size: 88.2*60*59mm Packaging box size: 152x119x79mm	
Packing list Camera*1, bracket*1, Type-C*1, manual*1, (solar panel*1, solar panel bracket*1 opt	
, and a second s	ional)