


BG67Q-UV			
Product Image			Product features
			★Stable 4G connection
			★Default working mode: AOV
			★Remote active wake-up, two-way voice intercom
			★Quick start, start recording within 400ms
			★Intelligent detection of human movement, intelligent alarm push
			★8000mAh battery powered, low battery reminder
			★Low power system optimization
			★1-day free cloud storage to save alarm videos
			★Black light night vision
			★AOV low power consumption, 24/7 recording
			★Low power and corded power compatible design
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	T412M
		Internal storage	1024MB
		Image sensor	SP4329 1/1.88 "Starlight grade CMOS sensor
		Minimum illumination	Color: 0.005 Lux, 0 Lux with Light
		Lens	Focal length 4mm, 1G7P F1.0 aperture
		Sensor performance	Supports digital WDR, 2D/3D noise reduction, and adaptive shutter speed
		PTZ	Horizontal 290°, Vertical 90°
		Viewing angle	D110° diagonal
3	Video	Night vision	Full color night vision, dual light source, 4 dual color lights
		Compression standard	Support H265/H264/JPEG
		Multi stream	Main stream: 2560×1440@15fps; Sub stream: 640×360@15fps
		Image adjustment	Vertical, horizontal adjustable, OSD display
4	Audio	Input	Built-in-38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G.711A codec standard, supports two-way voice and audio and video synchronization
5	AI	Humanoid detection	Humanoid detection, filtering invalid video content
		Area detection	Free daub, only monitoring the areas concerned by users
		Smart notification sound	Different devices push different sounds, so that you can know exactly which device is triggered
		Intelligent alarm sound	Set different equipment alarm sounds according to different scenarios
		More AI functions (testing)	Pets, vehicles, parcels, etc
6	Network	Networking	Use APP to scan the QR code on device to add; Use the device to scan QR code on APP to add
		Cat1 China	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41
		Cat4 Overseas	European/Japanese/US versions
7	Key	Key 1	On/Off key
		Reset key	long press to restore factory settings
8	Storage	External TF card	Support TF card (up to 256GB)
		Cloud storage	One-day free loop cloud storage
9	Alarm	Sound light alarm	Support
		Alarm detection	Support for human detection, PIR infrared human detection for 10 meters
10	Physical Indicators	Rated voltage	DC5V±5%
		Power supply	Built in 8000mAh battery
		Consumption	Sleep standby 300uA, working: 400MA-1.5A max
		Operating condition	Temperature: -10 ~ 55°C; Humidity: < 90%
		Weight	Net weight: 489g; Gross weight: TBD
		Size	Camera 233x109x133mm
		Packing list	Camera * 1, manual * 1, solar panel * 1, solar panel bracket * 1